

**Article number:** 906013

**Description:** Stegoband Classic Masking Tape

**EAN:** 8714247006382



## Colad Stegoband Classic Masking Tape

These special masking tape range is specifically developed for professional masking jobs in hard-to-reach places like glued or rubber-mounted windscreens or gaps between car parts. You do not need to disassemble windscreens for proper masking, it is a time saving solution.

The benefits of Colad Stegoband Classic Masking Tape:

- Masking Tape for hard to reach places
- For covering windshield and window rubbers and glued windshields
- Reinforced side to apply tape in between edges
- Protective paper liner on the adhesive part
- Easy removable, leaves no residu

---

### Packaging information

Per roll in a dispenserbox. 24 rolls per carton

---

### Technical information

- Color: White
- Width: 9 mm
- Temperature resistance: Max. 110°C for 60 minutes

---

### Frequently Asked Questions

> **How can I mask windshields, gaps and rubbers on a car?**

Colad Stegoband Classic Masking Tape is designed for masking jobs on hard-to-reach places. Just cut off the appropriate length, push the reinforced side under the rubber seal, fold the adhesive towards the area that should be covered, remove the paper liner and firmly apply the tape.

> **Is Stegoband Masking Tape heat resistance?**

The Stegoband Classic Masking Tape has a temperature resistance of max. 110°C for 60 minutes

## Related products



**9070xx**

Premium Masking Tape



**6365xxx**

Premium Masking Film



**2060xxx**

Masking Paper Premium



**9090**

Sensor Covers

### Disclaimer

It is the responsibility of the user to read, understand and apply the information contained in this data sheet. Products are for professional use only. Necessary protective equipment and clothing should be worn. Repairs should always be done in accordance with OEM guidelines and regulations. All information is for the user's consideration, investigation and verification. The specific use, application and conditions of use are beyond the control of EMM International BV. It is the responsibility of the user to determine the suitability of the product for the user's specific application.