

## Technical Data Sheet

### General

Article number: 000223

Description: Sander DS 40 Random Orbital Micro  
3.0 - 30 mm pad



### Specification

The machine is suited for efficient and simple removal of small irregularities and dried paint runs.

### Technical information

Size of pad: 50 mm (2")  
Weight: 700 g  
Speed: 16.000 r.p.m.  
Vibration level: 3.9 m/s<sup>2</sup>  
Air Inlet: ¼ inch  
Work pressure: 6.3 bar/ 90 psi  
Air consumption: 190 L/min (maximum air consumption)  
Sanding orbit: 3 mm  
Sound pressure: 88.4 dBA

### Accessories:

Standard:

Art.no. 022301 Standard: Mini pad (Hook & Loop) Ø 30 mm

Art.no. 009942 Machine Oil

Option:

Art.no. 022302 Mini pad (Adhesive) Ø 30 mm

### Remarks

Pneumatic mini random orbital sander for efficient polishing of paint defects.

The small support pad is easy to mount by turning it in the machine shaft.

Due to the small eccentric movement of this mini sander, the polishing scratches will be minimized but this is possible only if the correct structure of micro sanding discs is used.

After removing the irregularities, the small scratches can be removed with a mini polishing machine.

### Created by:

EMM International BV  
Bohemenstraat 19, 8028 SB Zwolle, The Netherlands  
[www.emm.com](http://www.emm.com)



T +31(0)38 467 66 00  
[www.hamach.com](http://www.hamach.com)