

## Declaration of Performance

CONSTRUCTION PRODUCTS REGULATION 2011  
DECLARATION OF PERFORMANCE

No. 202266

1. Unique identification code of the product-type:

**Asec AS10447, AS10448 Cylinder Sashlock, Asec AS10449, AS10450 Bathroom Lock, Asec AS10451, AS10452 Mortice Latch**

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4) of the CPR:

**Asec AS10447, AS10448 Cylinder Sashlock, Asec AS10449, AS10450 Bathroom Lock, Asec AS10451, AS10452 Mortice Latch**

3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

**For use on fire and smoke compartmentation doors**

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

**Aldridge Security  
Ltd, Unit H,  
Redfern Park Way,  
Birmingham,  
B11 2BF  
United Kingdom**

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

**N/A**

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V:

**System 1**

7. In case of the declaration of performance concerning a construction product covered by a harmonized standard:

**EN 12209: 2003 /AC 2005  
Notified testing laboratory No.1121 performed the type testing and issued test reports.  
Certificate of Constancy of Performance - 2812-CPR-AG7975**

8. European Technical Assessment:

**N/A**

9. Declared performance

Essential characteristics	Performance	Harmonised technical specification
<b>Self closing</b> <b>5.4.2 Closing force</b>	<b>Grade 8,</b> <b>≤ 200 Kg door mass, 15 N maximum</b> <b>closing force</b>	<b>EN 12209: 2003 /AC 2005</b>
<b>5.1.2 Re-latching force of latch bolt</b>	<b>&gt;2.5N</b>	
<b>Durability of self closing</b> <b>5.3.1 Durability of latch action</b>	<b>Grade M,</b> <b>≤ 200,000 test cycles, 25N side load on</b> <b>latch bolt.</b>	
<b>Ability to maintain the door in the closed</b> <b>position and not contribute to its spread</b> <b>of fire</b>	<b>Grade 1</b>	
<b>Control of Dangerous substances</b>	<b>If a reference to dangerous substances</b> <b>is added in the table ZA.1, the following</b>	

	<b>claim is suggested: Pass: the materials in the hinge do not contain or release any dangerous substances in excess of the maximum levels specified in existing European material standards or any national regulations (1)</b>	
--	--	--

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.  
Signed for and on behalf of the manufacturer by:



Chris Thorpe DIP GAI Minst  
Product Manager

Aldridge Security Ltd,  
Unit H,  
Redfern Park Way,  
Birmingham,  
B11 2BF  
United Kingdom  
13th September 2022