## SUPERLOCK DIGITAL RAPIDRESET SINGLE SIDED




- **10 second code change** Update the code fast with the code change button without taking the lock off the gate.
- G Easy to fit Slim 70mm (2 ¾") wide lock case along with adjustable and removable latchbolt ensure easy fitting to gates.
- G Easy to operate handle Designed particularly for those with mobility issues who find gripping and turning difficult.
- $\bigcirc$  Highly Secure The latchbolt moves 15mm (5/8") ensuring the bolt enters deep into the gatepost.
- G Hold-back function When the button on the back is activated to hold the lock in the open position.
- G Anti-climb handle This lock is also fitted with an anti-climb handle to prevent intruders using the handle as a foot hold to climb the gate.

## PRODUCT DETAILS GATEMASTER Product code: **Description: 7** BDGSRR1030L To fit 10-30mm (½" - 1 ¼") gate frames, left hand **8** BDGSRR1030R To fit 10-30mm (1/2" - 1 1/4") gate frames, right hand BDGSRR4060L To fit 40-60mm (1 ½" - 2 ¼") gate frames, left hand To fit 40-60mm (1 1/2" - 2 1/4") gate frames, right hand BDGSRR4060R OY CC

**BDGSRR** right hand version shown

## **INSTALLATION**

- 1. Drill 2 x 9mm (3/8") holes at 140mm (5  $\frac{1}{2}$ ") centres for fixing bolts provided.
- 2. Drill a 18mm (¾") clearance hole for the latchbolt at 60mm (2 3/8") centres up from the bottom fixing hole.
- 3. Fix the handles to the square spindles so that the handles are facing away from the latchbolt and secure using the hex key supplied.
- 4. Hold the lock against the back of the box section and screw on the latchbolt through the larger hole.
- Lock the latchbolt with the hex key supplied by inserting the hex key into the end of the latchbolt.
- Fix lock in place using the stainless steel bolt support plate and the countersunk screws provided. Ensure the latchbolt moves freely.
- 7. Fix strike plate by either welding or screw fixing onto the gate post
- MAINTENANCE Every 6 months, lubricate the latchbolt with light oil. Annually, dismantle the lock and spray mechanism with light oil.
- If you have any problems with the latch bolt sticking, drill out the latch bolt hole as this should alleviate the issue.





## **GATEMASTER**

VISIT GATEMASTERLOCKS.COM FOR MORE INFORMATION

