

SFX/8C-TY3-SCR-LSF-WHT

8 Core TCCA Type 3 Alarm Screened White LSF to BS4737-3.30:2015



Cable Construction	7 Cores	1 Core
Conductor	Tinned Copper Clad Aluminium	Tinned Copper Clad Aluminium
Conductor Diameter (mm)	0.20 ±0.008 x 7	0.20 ±0.008 x 7
Stranded Diameter (mm)	0.61	0.61
Insulation	PVC	PVC
Insulation Thickness (mm)	0.21	0.30
Insulation Diameter (mm)	1.00 ±0.100	1.20 ±0.100
Insulation Colours	Red,Black,Blue,Yellow,Green,White,Orange	Brown
Drain Wire		
Conductor	Tinned Copper Clad Aluminium	
Conductor Diameter (mm)	0.20 ±0.008 x 7	
Al-PET Shield	≥115%	
Nylon Rip-Cord	Yellow 210D	
Jacket	LSF	
Jacket Thickness (mm)	0.50	
Overall Diameter (mm)	4.60 ±0.200	
Jacket Colour	White RAL 9003	
Sheath Printing	(m)	
Reaction to Fire	Eca	
Electrical Characteristics		
Max Conductor DC resistance @ 20°C	155Ω/km	
Rated Temperature	80°C	
Rated Voltage	30V	
Insulation Resistance @20°C	>200 MΩ/km	