


SFX/6C-TY3-SCR-LSF-WHT

6 Core TCCA Type 3 Alarm Screened White LSF to BS4737-3.30:2015



Cable Construction	
	6 Cores
Conductor	Tinned Copper Clad Aluminium
Conductor Diameter (mm)	0.20 ±0.008 x 7
Stranded Diameter (mm)	0.22
Insulation	
	PVC
Insulation Thickness (mm)	0.21
Insulation Diameter (mm)	1.00 ±0.100
Insulation Colours	Red,Black,Blue, Yellow,Green,White
Drain Wire	
Conductor	Tinned Copper Clad Aluminium
Conductor Diameter (mm)	0.20 ±0.008 x 7
Al-PET Shield	>=115%
Nylon Rip-Cord	Yellow 210D
Jacket	LSF
Jacket Thickness (mm)	0.50
Overall Diameter (mm)	4.40 ±0.200
Jacket Colour	White RAL 9003
Sheath Printing	(m)
Reaction to Fire	Eca
Electrical Characteristics	
Max Conductor DC resistance @ 20°C	155Ω/km
Rated Temperature	-20°C to 80°C
Rated Voltage	30V
Insulation Resistance @20°C	>200 MΩ/km
Compliance and Standards	BS4737-3.30:2015,RoHS2 2011/65/EU
Application	For the interconnection of intruder alarm installations.