



CS106

Combined door entry and coded access (standalone) from **bell system**

The CS106 are combined door entry and coded access systems utilising an economic C106 standalone keypad module. These can be considered where a basic level of security is deemed to be adequate. Should a high level of security be necessary then the CS109 combined systems should be used

The C106 keypad may be programmed with up to ten unique access codes. If a valid code is entered on the keypad, the lock release will operate for a preset duration. The keypad has one green LED and one red LED to indicate the system status to the user: the green LED indicates that the lock release is operating, whilst the red LED indicates an invalid entry. There are ten user access codes and a wide range of programmable functions. Two panels are available: CP106 (SPA style) with a maximum of 7 buttons and the BL106 (bellini style) with a maximum of 6 buttons. For larger systems the CS109 combined systems should be used.

Model CS106-1
1 way system



Model CS106-4
4 way system



Standard combined system CS106 Series

Each system comprises of

- Model 801 wall mounting telephones
- Model CP106 aluminium door panel with integral keypad module
- Model 61 speech unit
- Model PS4A power supply
- Model 203 surface lock release
- Full installation and programming instructions

Model BLP106-3



CS106 Standalone Door Entry & Coded Access Combined Panel Dimensions CP106-1 to CP106-7 and CP106-1F to CP106-7F

Model CP106 front door panels

These panels are similar to the SPA style panels and are manufactured from 3mm anodised aluminium. They should be sited in a position that is protected from adverse weather conditions. They are available for either surface or flush fitting. The C106 keypad module is designed to complement the panel, push-button and surface box in a contemporary style. The module has outputs for both fail-safe and fail-secure lock releases and connection for an exit button.

The largest available panel is of 7 buttons and the CS109 series should be considered on any larger system.

Panel	Flush Panel (F)					Surface Panel		
	Panel (mm)		Backbox (mm)			Backbox (mm)		
	H	W	H	W	D	H	W	D
CP106-1	270	83	259	73	35	288	100	43
CP106-2	370	83	359	73	35	388	100	43
CP106-3	370	83	359	73	35	388	100	43
CP106-4	370	83	359	73	35	388	100	43
CP106-5	470	83	459	73	35	488	100	43
CP106-6	470	83	459	73	35	488	100	43
CP106-7	470	83	459	73	35	488	100	43

Sizes above 7 buttons are not available – see CS109.

Panel dimensions are approximate and may change without notice.