



# Door Closer Selector

Closer Type	Model	Accessibility	Fire & Certification			Performance		Installation Configuration	Hold-Open	Swing-Free	Control Options <small>All have Closing &amp; Latching Speed</small>		Strength	
		Accessibility (Assists Doc.M Contracts)	Fire Rating (mins)	Certification	CE & or UKCA	Max door weight (kg)	Max door width (mm)	Installed Pull / Push			Adjustable Back Check	Adjustable Delayed Action	Power Size	Power Adjustment
Surface Mounted	TS.3204	No	30-120	Certifire CF6018	CE & UKCA	60	950	Yes	Optional - Mechanical	n/a	Optional	n/a	EN3/4	By Template
	TS.4204	No	30-120	Certifire CF10138	CE & UKCA	80	1100	Yes	Optional - Mechanical	n/a	Yes	Optional	EN2-4	By Spring
	TS.5204	Yes Min Door Width 920mm Pull 887mm Push	30-120	Certifire CF6018	CE & UKCA	80	1100	Yes	Optional - Mechanical	n/a	Yes	Optional	EN2-4	By Spring
	TS.9205	Yes Min Door Width 835mm Pull 728mm Push	30-120	Certifire CF6144	CE & UKCA	110	1250	Yes	Optional - Mechanical	n/a	Optional	Optional	EN2-5	By Spring
	TS.9206	No	30-120	IFCC 1437	UKCA	120	1400	Yes	Optional - Mechanical	n/a	Yes	Yes	EN3-6	By Spring
Surface Mounted Slide Arm	TS.24	No	30-60	IFCC 1514	CE & UKCA	80	1100	Yes – Pull Yes – Push (with optional bracket)	Optional - Mechanical	n/a	n/a	n/a	EN2-4	By Spring
	TS.11204	Yes Min Door Width 857mm	30-120	Certifire CF6006	CE & UKCA	80	1100	Yes	Optional - Mechanical	n/a	Optional - Cushion Stop	n/a	EN2-4	By Spring
	TS.11205	Yes Min Door Width 757mm	30-120	Certifire CF6006	CE & UKCA	110	1250	Yes	Optional - Mechanical	n/a	Optional - Cushion Stop	n/a	EN2-5	By Spring
Electromagnetic	Responder 24	-	30-60	IFCC 1482	UKCA	80	1100	Yes	Yes	Yes	n/a	n/a	EN4	Fixed
	TS.FIRETRAK 115	-	30	IFCC 1513	UKCA	110	1250	Yes	Yes	n/a	n/a	n/a	EN2-5	By Spring
Overhead Concealed	ITS.11204.2.5	Yes Min Door Width 835mm	30-60	Certifire CF5902	CE & UKCA	130	1100	n/a	Optional - Mechanical	n/a	Optional - Cushion Stop	n/a	EN2-4	By Spring

Products may be fitted on previously tested door and frame with relevant intumescent as required. For particular conditions feel free to visit our website [www.rutlanduk.co.uk](http://www.rutlanduk.co.uk) or contact our dedicated technical support team on: 01246-261491 if you have any further question.