

FUCHS GEAR LUBE AEROSOL

An advanced open gear lubricant in aerosol form

Description

GEAR LUBE is a spray lubricant from the FUCHS Lubricants (UK) range of industrial aerosol packaged products. It is a dark coloured, highly adhesive product reinforced with solid lubricants designed for application to industrial open gears.

The product deposits a tenacious lubricating film with outstanding anti-wear properties. It is designed for application to open gears that mesh precisely and require this type of film lubrication. Its highly adhesive character is designed to reduce or eliminate throw-off in use.

Application

FUCHS GEAR LUBE AEROSOL is for use on all exposed gears and other moving parts and is resistant to 'fling-off' during use. It has exceptional penetrating power and water resistance and is ideal for use on equipment such as heavy duty chains and steel cables, or other such applications that are constantly exposed to the weather.

FUCHS GEAR LUBE AEROSOL sprays to produce a frothy brown /black high viscosity solvent and oil blend. The solvent promotes excellent penetration into wire ropes and gear chains to produce effective lubrication. The residual film is kept pliable by the mineral oil content and resists water wash off, making it ideal for used in exposed conditions.

Advantages/Benefits

- Large 500ml aerosol can
- Excellent anti-wear characteristics
- May be applied to moving gears
- Protects against corrosion
- Repels moisture
- Contains no CFC propellants - ozone friendly



April 2010 GDUK Page 1 of 2

Directions for Use

Shake the can thoroughly before use.

Hold in an upright position, spraying directly onto the component surface from a distance of 8-12 inches.

The highly directional button ensures accurate positioning of the lubricant.

Always ensure any guarding is in place when treating moving equipment.

Re-apply as required.

Caution

- Pressurised container
- Protect from sunlight and do not expose to temperatures exceeding 50°C
- Do not pierce or burn, even after use
- Do not spray on a naked flame, or any incandescent material

NOTE

Follow the safety information printed on the cans to ensure safe application.

CHARACTERISTICS: FUCHS GEAR LUBE AEROSOL

Characteristics	Unit		Test Method
Specific gravity of base material		0.94 - 0.99	IP160
Specific gravity of total aerosol contents (including propellant) at 15.6°C		0.772	IP160
Viscosity of base material (including diluent) at 20°C	cPs	150	IP71
Fill weight of 500ml aerosol	g	386	