

Product Information

MOVING YOUR WORLD



SILKUT COMPOUND 1000

Paste for severe tapping application

Description

SILKUT COMPOUND 1000 is a soft paste and contains a high proportion of fatty and extreme pressure additives together with a solid lubricant. This product may stain cuprous and some other non-ferrous materials.

Application

It is primarily intended for use on medium and high tensile steels where the lubricant is applied by dipping or brushing the tap. It is particularly recommended for the more severe operations on fine threads.

Advantages/Benefits

- Possesses a high EP capability.
- It can be readily removed by paraffin or other hydrocarbon solvents.

Component Protection

Following manufacturing operations Fuchs recommends the use of our fully compatible RENOCLEAN cleaners and ANTICORIT corrosion preventives to clean and protect your components. Please refer to data sheets or contact your local Fuchs Area Manager to discuss your requirements.

Product Information

MOVING YOUR WORLD



CHARACTERISTICS: SILKUT COMPOUND 1000

Characteristics	Unit	Value	Test Method
Appearance		Firm yellow/green paste	
Odour characteristics		Lanolin	
Sap matter	%wt	35.0	IP284
Reactive sulphur	%wt	10.0	IP155
Sulphated ash	%wt	15.0	IP163
Fillers	%	25.0	(DEF 2000 No.13)

Notes

The information contained in this product information is based on the experience and know-how of FUCHS LUBRICANTS (UK) plc in the development and manufacturing of lubricants and represents the current state-of-the-art. The performance of our products can be influenced by a series of factors, especially the specific use, the method of application, the operational environment, component pre-treatment, possible external contamination, etc. For this reason, universally valid statements about the function of our products are not possible.

Our products must not be used in aircraft or spacecraft. Our products may be used in manufacture of components for aircraft or spacecraft if they are removed without residue from the components prior to assembly into the aircraft or spacecraft.

The information given in this product information represents general, non-binding guidelines. No warranty expressed or implied is given concerning the properties of the product or its suitability for any given application. We therefore recommend that you consult a FUCHS LUBRICANTS (UK) plc application engineer to discuss application conditions and the performance criteria of the products before the product is used. It is the responsibility of the user to test the functional suitability of the product and to use it with the corresponding care.

Our products undergo continuous improvement. We therefore retain the right to change our product program, the products, and their manufacturing processes as well as all details of our product information sheets at any time and without warning, unless otherwise provided in customer-specific agreements. With the publication of this product information, all previous editions cease to be valid. Any form of reproduction requires express prior written permission from FUCHS LUBRICANTS (UK) plc.

© FUCHS LUBRICANTS (UK) plc. All Rights reserved.