

METRIC FINE THREAD RING GAGE

- Class 6g
- Standard ISO1502
- Material: OHNS (Oil Hardened Non-shrinking Steel), stable dimension and wear resistance
- Hardness HRC60-62



4632-10Q



4632-10QN

Code (GO)	Code (NOGO)	Size (mm)
4632-8G *	4632-8GN *	M8x0.5
4632-8L *	4632-8LN *	M8x0.75
4632-8P *	4632-8PN *	M8x1
4632-10L *	4632-10LN *	M10x0.75
4632-10P *	4632-10PN *	M10x1
4632-10Q *	4632-10QN *	M10x1.25
4632-12P *	4632-12PN *	M12x1
4632-12Q *	4632-12QN *	M12x1.25
4632-12R *	4632-12RN *	M12x1.5
4632-14P *	4632-14PN *	M14x1
4632-14Q *	4632-14QN *	M14x1.25
4632-14R *	4632-14RN *	M14x1.5
4632-16P *	4632-16PN *	M16x1
4632-16R *	4632-16RN *	M16x1.5
4632-18P *	4632-18PN *	M18x1
4632-18R *	4632-18RN *	M18x1.5
4632-20P *	4632-20PN *	M20x1
4632-20R *	4632-20RN *	M20x1.5

Code (GO)	Code (NOGO)	Size (mm)
4632-22R *	4632-22RN *	M22x1.5
4632-24P *	4632-24PN *	M24x1
4632-24R *	4632-24RN *	M24x1.5
4632-24T *	4632-24TN *	M24x2
4632-25R *	4632-25RN *	M25x1.5
4632-26R *	4632-26RN *	M26x1.5
4632-27R *	4632-27RN *	M27x1.5
4632-27T *	4632-27TN *	M27x2
4632-28R *	4632-28RN *	M28x1.5
4632-30P *	4632-30PN *	M30x1
4632-30R *	4632-30RN *	M30x1.5
4632-30T *	4632-30TN *	M30x2
4632-32R *	4632-32RN *	M32x1.5
4632-33R *	4632-33RN *	M33x1.5
4632-33T *	4632-33TN *	M33x2
4632-35R *	4632-35RN *	M35x1.5
4632-36R *	4632-36RN *	M36x1.5
4632-36T *	4632-36TN *	M36x2

Code (GO)	Code (NOGO)	Size (mm)
4632-38R *	4632-38RN *	M38x1.5
4632-40R *	4632-40RN *	M40x1.5
4632-40T *	4632-40TN *	M40x2
4632-42R *	4632-42RN *	M42x1.5
4632-42T *	4632-42TN *	M42x2
4632-45R *	4632-45RN *	M45x1.5
4632-45T *	4632-45TN *	M45x2
4632-48R *	4632-48RN *	M48x1.5
4632-48T *	4632-48TN *	M48x2
4632-50R *	4632-50RN *	M50x1.5
4632-50T *	4632-50TN *	M50x2
4632-52R *	4632-52RN *	M52x1.5
4632-52T *	4632-52TN *	M52x2
4632-55R *	4632-55RN *	M55x1.5
4632-55T *	4632-55TN *	M55x2
4632-58R *	4632-58RN *	M58x1.5
4632-60T *	4632-60TN *	M60x2

* Supplied with manufacturer calibration certificate