

METRIC FINE THREAD PLUG GAGE



- Class 6H
- Standard ISO1502
- Material: OHNS (Oil Hardened Non-shrinking Steel), stable dimension and wear resistance
- Hardness HRC60-62

4642-12R

Code	Size (mm)
4642-8G *	M8x0.5
4642-8L *	M8x0.75
4642-8P *	M8x1
4642-10L *	M10x0.75
4642-10P *	M10x1
4642-10Q *	M10x1.25
4642-12P *	M12x1
4642-12Q *	M12x1.25
4642-12R *	M12x1.5
4642-14P *	M14x1
4642-14Q *	M14x1.25
4642-14R *	M14x1.5
4642-16P *	M16x1
4642-16R *	M16x1.5

Code	Size (mm)
4642-18P *	M18x1
4642-18R *	M18x1.5
4642-20P *	M20x1
4642-20R *	M20x1.5
4642-22R *	M22x1.5
4642-24P *	M24x1
4642-24R *	M24x1.5
4642-24T *	M24x2
4642-25R *	M25x1.5
4642-26R *	M26x1.5
4642-27R *	M27x1.5
4642-27T *	M27x2
4642-28R *	M28x1.5
4642-30P *	M30x1

Code	Size (mm)
4642-30R *	M30x1.5
4642-30T *	M30x2
4642-32R *	M32x1.5
4642-33R *	M33x1.5
4642-33T *	M33x2
4642-35R *	M35x1.5
4642-36R *	M36x1.5
4642-36T *	M36x2
4642-38R *	M38x1.5
4642-40R *	M40x1.5
4642-40T *	M40x2
4642-42R *	M42x1.5
4642-42T *	M42x2
4642-45R *	M45x1.5

Code	Size (mm)
4642-45T *	M45x2
4642-48R *	M48x1.5
4642-48T *	M48x2
4642-50R *	M50x1.5
4642-50T *	M50x2
4642-52R *	M52x1.5
4642-52T *	M52x2
4642-55R *	M55x1.5
4642-55T *	M55x2
4642-58R *	M58x1.5
4642-60T *	M60x2

* Supplied with manufacturer calibration certificate