

DIAL BORE GAGE



- Dial indicator graduation: metric 0.01mm
inch 0.0005"
- Dial indicator range: metric 0-3mm
inch 0-0.25"
- Ceramic moving tip and anvil except moving tip and anvil of 6-10mm/0.24-0.4", moving tip of 10-18mm/0.4-0.7", moving tip of 18-35mm/0.7-1.5"
- Packed in blow mould case or wooden box

Code	Range	Depth	Dial indicator bezel	Anvil type
2322-10	6-10mm	40mm	42mm	A
2322-18	10-18mm	100mm	42mm	B
2322-35	18-35mm	150mm	58mm	C
2322-50	35-50mm	150mm	58mm	D
2322-100	50-100mm	150mm	58mm	D
2322-160	50-160mm	150mm	58mm	D
2322-250	160-250mm	400mm	58mm	D
2322-450	250-450mm	400mm	58mm	D
Code	Range	Depth	Dial indicator bezel	Anvil type
2323-04	0.24-0.4"	1.57"	2.28"	A
2323-07	0.4-0.7"	4"	2.28"	B
2323-15	0.7-1.5"	6"	2.28"	C
2323-24	1.4-2.4"	6"	2.28"	D
2323-4	2-4"	6"	2.28"	D
2323-6	2-6"	6"	2.28"	D
2323-10	6-10"	16"	2.28"	D
2323-16	10-16"	16"	2.28"	D