

TECHNICAL DATA SHEET



Product code: see below table **Sector:** Industrial **Issue No:** 4 **Issue Date:** 18/08/22

MILLGEAR SY RANGE

The Millgear SY range are fully synthetic, polyalkylene glycol (PAG) extreme pressure industrial gear lubricants.

Application

Use as received for a wide range of industrial gears, oven conveyor chains, tenters, stenters and applications with elevated temperatures.

Note: This lubricant should not be mixed with mineral oils, when changing over from mineral based products, flush the system with the suitable Millgear SY product.

Features & Benefits

- Performs at elevated temperatures, typically in excess of 200C.
- High viscosity index imparts low start up drag whilst maintaining optimum viscosity at operating temperature.
- Low oxidation leads to extended oil life, typically 10,000 hours @ 100C.
- Excellent Corrosion protection of yellow and ferrous metals.
- David Brown type G general approval.

Performance Profile

Millgear SY	220	320	460	680
EP/Load Carrying	FZG load stage 12			
Timkin OK Load lbs	27	35	35	
Weld Load Kg	>160	>160	>160	
Copper Strip Corrosion	1a	1b	1a	1b

Rust Prevention

Distilled Water	Pass	Pass	Pass	Pass
Synthetic Sea Water	Pass	Pass	Pass	Pass



MADE IN BRITAIN

Millers Oils Ltd
Brighouse West Yorkshire HD6 3DP UK
Tel: +44(0) 1484 713201
www.millersoils.co.uk

TECHNICAL DATA SHEET



Typical Characteristics

Millgear SY	220	320	460	680
Specific Gravity @ 15°C	1.006	1.005	1.076	1.076
Kinematic Viscosity @ 100°C	31.8cSt	44.8cSt	63.7cSt	112.4
Kinematic Viscosity @ 40°C	237cSt	325cSt	433cSt	680cSt
Viscosity Index	178	197	222	265
Pour Point (°C)	-30	-30	-28	-33
Flash Point (°C)	231	225	225	265
Neutralisation Number mg KOH/g (IP 139)	0.6	0.6	0.65	
Health & Safety/Product Code	5327	5501	5380	7768

Technical & Health and Safety

T: 01484 475060

E: technical@millersoils.co.uk

For H&S info or SDS, please visit our website www.millersoils.co.uk



MADE IN BRITAIN

Millers Oils Ltd
Brighouse West Yorkshire HD6 3DP UK
Tel: +44(0) 1484 713201
www.millersoils.co.uk