

Ophelia Pull Out Spray

Product Finish: Chrome Product code: AT2074
EAN13 barcode: 5060344155960



Product features:

- · Supplied compete with flexible tail pipes for fast simple fitting
- Single lever control for effortless single handed control
- · Single spray pattern showerhead
- · Solid and functional European architect design styling
- · Antisplash spout supplied as standard


Additional information / Parts included:

SCO06050 fixing kit

The installation of this product should respect requirement IRN R090.

Note: the image shown may not reflect the product finish, chrome finish is typically depicted.

Product dimensions:



- Overall Height / projection: 478 mm
- Exit reach: 195 mm
 Exit height: 163 mm
 Centre distance(s):
- Base diameter(s): 48 mm
- Recommended hole diameter: Ø 35 mm
- Max. surface depth: 50 mm
- Spout diameter: 19 mm
 Spout aerator size: M24F


Packaged properties:

Box length: 435mm Box depth: 70mm

Box width: 340mm Units per outer: 5

Tap only weight: 1.77kg Boxed weight: 2.50kg

Product flow characteristics:



- Min / Max water pressure: 0.75 / 5.50 bar
- Recommended / Max water temperature: 46°C / 70°C
- Part G Mixed flow rate at 3 bar (litres / min): 11.69
- Control valve type: Single lever ceramic cartridge
- Product flow characteristics: Single flow
- Non return valve(s): Hot & cold (integral to tails), 1 x in spray head
- Aerator type: Honeycomb aerator
- Accepts revolve / spray areator: No
- Spout connection method: Grub screw
- Tail pipe inlet / outlet size: M10 / 1/2" BSP Male
- Inlet pipe type / length: flexible stainless braided hose / 360 mm

Care instructions summary

- Clean the mixers and showers regularly as required, using soap, do not use any other cleaners.
- Regular cleaning will prevent the build-up of lime scale and dirt
 After cleaning rinse thoroughly with clean water to remove any cleaner residue
- Residues of sink & worktop cleaners can also cause damage, so rinse with clean water after
- using, avoid contact with any abrasives
- Warranty Summary (Full details available on request)
- Materials and workmanship defects warranted for 5 years
- Valves and working parts warranted for 5 years
 Surface warranty defects warranted for 1 year
- O-rings, hoses & gaskets warranted for 1 year