

## Euphoria

## Wall Mounted Thermostatic Post Shower with Hose & Shower Handset



## Product features:

- Metal & ABS construction
- · Leading design features requiring high pressure
- Thermostatic valve for safety & comfort
- · Single spray pattern showerhead
- · Swivel showerhead connector for maximum flexibility

Packaged properties:


Box length (mm): 1260 Box depth(mm): 200

Box width(mm): 550 Boxed weight (Kg): 16.6

Includes pop up waste?: No Additional comments:

Includes 3mm allen key, ABS handshower

**Product dimensions:** 



• Product mounted where: Wall

Recommended hole size:

• Overall Height / projection: 390 mm
• Exit reach: 1702 mm
• Exit height: 63 mm
• Base size:

• Inlet centre distance(s):


• Min. fitting depth required:

60 mm

150 ± 20 mm

• Max. surface depth:

**Product flow characteristics:** 



- Min / Max water pressure (bar): 1.50\* / 5.00
- Part G max. mixed flow rate at 3 bar (I/m): 13.9
- Inlet connection type / length: Eccentric / mm
- Inlet (plumbing connection) / outlet size: 1/2" M / 3/4" M
- Product flow characteristics:

Non return valve(s) supplied or position: h&c inlet & shower snodo

- · Aerator type:
- Control valve type: Thermostatic ()
   Includes output diverter?: Yes
- $\bullet \ \textbf{Inlet meshed particle filters included:} \ 0.60 \ \text{mm} \\$
- Shower hose type / length: Smoothflex / 1.50 m

Warranty Summary (full details available on request):

- Materials and workmanship defects warranted for 5 years
- Valves and working parts warranted for 5 years
   Surface warranty defects warranted for 1 year
- O-rings, hoses & gaskets warranted for 1 year

## Care instructions:

- Clean the mixers and showers regularly as required, using soap, do not use any other cleaners.
- Regular cleaning will prevent the build up of lime scale and dirt
- After cleaning rinse thoroughly with clean water to remove any cleaner residue
- Residues of liquid soaps, shampoos and shower foams can also cause damage, so rinse with clean water after using, avoid contact with any abrasives