

Opulence Bath Pillar Taps



Product features:


- · Metal construction throughout
- Custom designed for lower range pressures
- · Luscious European quality chromium plate finish
- · Fixed spout to prevent accidental water damage
- · Traditional European styling

Packaged properties:

Box length (mm): 255 Box depth(mm): 95
Box width(mm): 200 Boxed weight (Kg): 2.2

Includes pop up waste?: No Additional comments:

Product dimensions:




Product mounted where: Surface
 Recommended hole size: 35 mm

Overall Height / projection: 145 mm
Exit reach: 85 mm
Exit height: 55 mm
Base size: 55 mm

• Inlet centre distance(s): n/a mm

• Min. fitting depth required: 0 mm • Max. surface depth: 40 mm

Product flow characteristics:



- Min / Max water pressure (bar): 0.10* / 5.5
- Part G max. mixed flow rate at 3 bar (I/m): 83.02
- Inlet connection type / length: Fixed / 50 mm
- Inlet (plumbing connection) / outlet size: 3/4" M / n/a
- Product flow characteristics: Single flow Non return valve(s) supplied or position: n/a
- Aerator type: Flow straightener
- Control valve type: 3/4 QT CD (8-20)
 Includes output diverter?: N/A
- Inlet meshed particle filters included: n/a
 Shower hose type / length: N/a / n/a

Warranty Summary (full details available on request):

- Materials and workmanship defects warranted for 5 years
- Valves and working parts warranted for 5 years
- Surface warranty defects warranted for 1 year
- O-rings, hoses & gaskets warranted for 1 year

Care instructions:

- Clean the mixers and showers regularly as required, using soap, do not use any other cleaners.
- Regular cleaning will prevent the build up of lime scale and dirt
- After cleaning rinse thoroughly with clean water to remove any cleaner residue
- Residues of liquid soaps, shampoos and shower foams can also cause damage, so rinse with clean water after using, avoid contact with any abrasives