

Sandon - 1.5 Bowl

White Glaze



Product Basics:



note: model shown may not be displayed in the finish as described

Product code	AW1033
EAN 13 barcode	5060344156370
Specification version	1 04/11/2025
Finish	White Glaze
Notes: Ceramic is a natural hand finished material, you should expect variances in product finishes and sizes	

Included parts:

 2 x AX1002 (m) 90mm (1.5") Orbit manual basket strainer waste - long bolt	 1 x AX1105 (m) Rectangular overflow (55x30mm vertical)	 1 x AX1009-1 (m) 2 Bowl Pipework	 1 x AX4003 (m) Fitting & care instructions & data sheet - ceramic undermount	

Recommended parts & accessories:

--	--	--	--	--

Packing summary:

- Packaging Type: Boxed
- Packaged size LxWxD: 650x575x300
- Gross weight (ea): 24.7Kg
- Net weight (ea): Kg

Warranty summary:

Details of warranty duration and terms & conditions for each product type can be found on our website: abodedesigns.co.uk/support/warranty

Certain products may benefit by registering the warranty here: abodedesigns.co.uk/support/register/warranty



Care summary:

- Clean the products regularly using soapy water and a non-abrasive cloth, regular cleaning will prevent the build-up of lime scale and dirt.
- Regular cleaning will prevent the build-up of lime scale and dirt.
- After cleaning rinse thoroughly with clean water to remove any cleaner residue.
- Avoid contact with any harsh chemical or abrasives, for more detail see supplied booklet or www.abodedesigns.co.uk


Mounting dimensions:

Type of Installation	Installation type recommended?	Recommended minimum base unit mm (20mm wall thickness)	Cut out size (length x width x corner radius mm)	Overall recessed fitting width mm (required for bowl(s), tap hole, overflow)	Minimum – Maximum worktop thickness (mm)	Additional fitting notes
Inset	Yes	800	575 x 440 R30	560		
Undermount	Yes	800	547 x 412 R16	560		
Apron Front	No					
Flushmount	No					


Overall product size (mm):	595x460x220 corner radius 40
-----------------------------------	------------------------------



INSET CUT OUT



UNDERMOUNT CUT OUT




We do not recommend use of instant hot water taps for this type of sink, repeated use may prematurely age the sink surface.

The dimensions on ceramic fireclay products are subject to wider tolerances due to the nature of this natural material and the firing process.

***Important fabricator notes for Undermount, Apron Front & Flushmount sinks:**

The cut out size indicated is aligned with outside edge of the bowl top radius (similar to the example below):



You should confirm with your client if the worksurface cutout is to be cut flush, inside or outside this suggested perimeter shape & size.

If you create the cutout smaller or larger than the indicated size then the fit of the accessories may be affected and should be physically checked.

General:

All details are provided in good faith but do not include the tolerances of the material or manufacturing process.

We request that a test cutout is made in scrap timber and checked against the actual sink to be installed before committing to cutting the final worksurface.

Abode can not accept liability for problems or costs incurred by failure to follow this request.

CAD cutout files can be downloaded from
www.abodedesigns.co.uk

Bowl & drainer details:	Bowl 1 (typically main bowl):	Bowl 2: (typically ⅓ or ¼ or 2nd main bowl):	Bowl 3:	Drainer (left)	Drainer (right)
Bowl Size Width x Length x Depth x Radius (mm)	337 x 400 x 175 R10	183 x 400 x 175 R10			
Bowl floor radius (mm)	10	10			
Wastehole diameter (mm)	90	90			
Overflow type	Rectangular flush				
Wall thickness (gauge mm)	12	12			
Bowl volume (apx. litres)	21.5	11.1			
Bowl texture / finish	Glazed	Glazed			



UK: Norcros Group (Holdings) Ltd. T/A Abode, Ladyfield House, SK9 1BU, UK. info@abodedesigns.co.uk
EU: MIL, Unit 8 Purcellsinch Ind Est, Dublin Road, Kilkenny, R95 HP71, Ireland. euinfo@abode.eu