

# Oxbury Bridge

Product code: AT2225 Product Finish: **Antique Brass** EAN13 barcode: 5060879994492



### **Product features:**

Victorian inspired aesthetic

Quarter turn handle action for precise flow control

Ceramic handle(s) as standard

Flow Limited to 5 Litres per Minute for Part G compliance


Supplied with adjustable centre inlets

#### Additional information / Parts included:

Includes additional Honeycomb 1.5gpm, Solid metal handle addition

Note: the image shown may not reflect the product finish, chrome finish is typically depicted

#### **Product dimensions:**



• Overall, Height / projection: 402 mm

• Exit reach: 223 mm • Exit height: 253 mm

• Centre distance(s): 149-257 (203 centres) mm

• Base diameter(s): 45 mm

Recommended hole diameter: Ø 35 mm

• Max. surface depth: 50 mm

• Spout diameter: 20 mm Spout aerator size: M22 x 1


#### Packaged properties:

Box length: 575mm Box depth: 80mm

Box width: 350mm Units per outer: 5

Boxed weight: 2.88kg Tap only weight: 1.98kg

## **Product flow characteristics:**



- Min / Max water pressure: 0.20 / 5 bar
- Recommended / Max water temperature: 46°C / 70°C • Part G - Mixed flow rate at 3 bar (litres / min): 19.31
- Control valve type: Ceramic disc QT • Product flow characteristics: Single flow
- Non return valve(s): None
- Aerator type: Honeycomb Aerator · Accepts revolve / spray areator: No
- Spout connection method: Grub screw
- Tail pipe inlet / outlet size: N/A / 1/2" BSP Male
- Inlet pipe type / length: Fixed threaded inlets / 120 mm

- Clean the mixers and showers regularly as required, using soap, do not use any other cleaners.
- Regular cleaning will prevent the build-up of lime scale and dirt After cleaning rinse thoroughly with clean water to remove any cleaner residue
- Residues of sink & worktop cleaners can also cause damage, so rinse with clean
- using, avoid contact with any abrasives
- Warranty Summary (Full details available on request)
- Materials and workmanship defects warranted for 5 years
- Valves and working parts warranted for 5 years Surface warranty defects warranted for 1 year
- O-rings, hoses & gaskets warranted for 1 year