



## Product features:

- Stylish two tone brushed acents
- Part G compliant 5 Litres / minute flow rate
- · Modern minimalism with flair
- Wall mounting box for easier installation
- Cold start valve


Packaged properties:

Box length (mm): Box depth(mm):

Box width(mm): Boxed weight (Kg):

Includes pop up waste?: No Additional comments:

## **Product dimensions:**



• Product mounted where: 0 mm


• Recommended hole size:

Overall Height / projection: 220 mm
Exit reach: 200 mm
Exit height: 42 mm
Base size: 250 x100 mm

• Inlet centre distance(s):

• Min. fitting depth required: 0 mm • Max. surface depth: n/a

# **Product flow characteristics:**



- Min / Max water pressure (bar): 0.40\* / 5
- 0.4 bar (basin without limiter).
- 1 bar (basin with limiter).
- 1.2 bar (bath with high flow aerator)

flow rate varies depending on aerator install choice (high flow aerator supplied for bath filling for low supply pressures), see graph for details

- Part G max. mixed flow rate at 3 bar (I/m): 4.95
- Inlet connection type / length: N/a / 0 mm
- Inlet (plumbing connection) / outlet size: 1/2" F / n/a
- Product flow characteristics: Single flow Non return valve(s) supplied or position: no
- Aerator type: 5 L/M, honeycomb, swivel & high flow option for bath filling (or low pressure supplies)

# Warranty Summary (full details available on request):

- Materials and workmanship defects warranted for 5 years
- Valves and working parts warranted for 5 years
- Surface warranty defects warranted for 1 year
- O-rings, hoses & gaskets warranted for 1 year

#### Care instructions

- Clean the mixers and showers regularly as required, using soap, do not use any other cleaners.
- Regular cleaning will prevent the build-up of lime scale and dirt
- After cleaning rinse thoroughly with clean water to remove any cleaner residue
- Residues of liquid soaps, shampoos and shower foams can also cause damage, so rinse with clean water after using, avoid contact with any abrasives