

Product Finish: Stainless Steel

Product code: AT2178
EAN13 barcode: 5060879990173




Note: the image shown may not reflect the product finish, chrome finish is typically depicted.

Product features:

- 304 grade brushed stainless steel construction
- Single lever control for effortless single handed control
- Supplied complete with flexible tail pipes for fast simple fitting
- Modern minimalism with flair
- Antisplash spout supplied as standard

Additional information / Parts included:

Product dimensions:



- Overall Height / projection: 377 mm
- Exit reach: 200 mm
- Exit height: 259 mm
- Centre distance(s):


- Base diameter(s): 50 mm
- Recommended hole diameter: Ø 35 mm
- Max. surface depth: 45 mm

- Spout diameter: 24 mm
- Spout aerator size: M22 Female

Packaged properties:

- Box length: 460mm
- Box depth: 60mm
- Box width: 290mm
- Units per outer: 5
- Tap only weight: 1.44kg
- Boxed weight: 2.70kg

Product flow characteristics:



- Min / Max water pressure: 0.50 / 5.5 bar
- Recommended / Max water temperature: 46°C / 70°C
- Part G - Mixed flow rate at 3 bar (litres / min): 12.63

- Control valve type: Single lever ceramic cartridge
- Product flow characteristics: Single flow
- Non return valve(s): None

- Aerator type: Neoperl Honeycomb
- Accepts revolve / spray areator: No
- Spout connection method: Grub screw

- Tail pipe inlet / outlet size: M10 / 1/2" BSP Female
- Inlet pipe type / length: Flexible stainless braided hose / 600 mm

Care instructions summary:

- Clean the mixers and showers regularly as required, using soap, do not use any other cleaners.
- Regular cleaning will prevent the build-up of lime scale and dirt
- After cleaning rinse thoroughly with clean water to remove any cleaner residue
- Residues of sink & worktop cleaners can also cause damage, so rinse with clean water after using, avoid contact with any abrasives

Warranty Summary (Full details available on request):

- Materials and workmanship defects warranted for 5 years
- Valves and working parts warranted for 5 years
- Surface warranty defects warranted for 1 year
- O-rings, hoses & gaskets warranted for 1 year