


SYNDEO Angled Beam Vertical Bend LED Flex

24V - 14.4mm x 6mm - Vertical Bend - IP54

tagra®

SKU: PPS24-NEONASYMM



24V



IP54

5M

5YR
Warranty

Key Features

- Available in 2700K & 3000K
- Cut Anywhere
- Vertical Bend
- 500mm Syndeo Cable
- Up to 682 Lumens per metre
- 120° Beam Angle (directed at 30°)
- Adhesive Backing
- Silicone
- 5 Metre Max. Run Length
- Available in 5M reels
- 5 Year Warranty

Electrical Data

Voltage	Max. Current	Typ. Current	Current 5M	Max. Power	Typ. Power	Power 5M
24V	0.5A/m	0.5A/m	2.5A	11.5W/m	10.5W/m	52.5W


Photometric Data

Colour Temperature	CCT/Wavelength	Lumens/m	LED Chip	LEDs/m	LEDs/unit
Very Warm White	2700K	619lm	2216	300 LEDs	-
Warm White	3000K	682lm	Cut Points	CRI	Beam Angle
			-	>90	120°
			SDCM	Dimmable	IC Type
			<3	Yes	
			Pixels/m	Pixels/unit	PWM Rate

Mechanical Data

Min. Bend Diameter	Bend Direction	Cable Length	Cable End	Cable Type	Wire Colours
100mm	Vertical	500mm	Double	20 AWG	WHITE V+ DC
IP Rating	IK Rating	Material	Operating Temperature		WHITE DASHED V- DC
IP54	IK04	Silicone	-20°C ~ 45°C		
Lifespan	Energy Rating	Warranty	Dimensions		
50,000 Hours	-	5 Years	W14.4mm x H6mm		

Dimensions



Available SKUs

SKU	CCT	IP Rating	Length
PPS24-27KASYMM5MKIT	2700K	IP54	5000mm
PPS24-27KASYMM5MKIT	3000K	IP54	5000mm

Available Accessories

Type	SKU	Colour/Material	Note
End Cap	NEONASYMM-ENDCAPS-TOP	Silicone	Pack of 16, 8 Pairs