


Silicone LED Cable

5 Cores - Max. 3 Amps - Silicone - 0.35mm²

tagra®

SKU: SILCBL-5C



3A
Max.
Per Core

5
Core


SIL

RGB
+W

Key Features

- ▶ 3A Current Capacity
- ▶ 60V Voltage Rating
- ▶ Black or White
- ▶ Silicone
- ▶ 10M, 50M & 100M
- ▶ 0.35mm² Conductor

Dimensions



Product Data

Conductor Cores	Conductor Cross Section	Current Rating	Dimensions
5x (13/0.18mm)	0.35mm ²	3.0A per core	Ø5.8mm
Cable Gauge	Cable End	Cable Sheath	Cable Jacket
22 AWG	Tinned Copper	Silicone	White or Black
Voltage Rating	Operating Temp	Flame Retardant	Min. Bend Radius
Max. 60V	-60°C ~ +200°C	FT-2	30mm

Wire Colours	
Black	V+
Red	R-
Green	G-
Blue	B-
White	W-

Available SKUs

SKU	Colour	Shape	Length
SILCBL-5C-10M-B	Black	Round	10000mm
SILCBL-5C-50M-B	Black	Round	50000mm
SILCBL-5C-100M-B	Black	Round	100000mm

SKU	Colour	Shape	Length
SILCBL-5C-10M-W	White	Round	10000mm
SILCBL-5C-50M-W	White	Round	50000mm
SILCBL-5C-100M-W	White	Round	100000mm