

Data Sheet

Product Code: XDB5UACBS

Product Description: 2-Gang 13A Single Pole Switched Socket with

1x USB A & 1x USB C Charging Ports

Range: Screwless

Finish: Brushed Brass

Product Category: Sockets with USB Charging

Insert/Knob Colour: Brass Rocker

Barcode: 5021575008999

Dimensions: 86x147x31mm

Faceplate Depth: 4mm

Net Weight: 199g

Gross Weight: 172g

Fixing Centres: 120.6mm

Depth from Mounting Face: 23.1mm

Recommended Back Box Depth: 35mm

Operating Voltage: $230v\ 50Hz$

Maximum Load Rating: 13A Socket, 20W Shared USB Charging

Maximum Current Rating: 13A

Terminal (Live) Diameter: 4.8 mm; Capacity: $4 \times 2.5 \text{mm}^2$

Terminal (Neutral) Diameter: 4.8mm; Capacity: 4 x 2.5mm²

Terminal (Earth) Diameter: 4.8 mm; Capacity: $4 \times 2.5 \text{mm}^2$

Intended Applications: Indoor Use Only. Domestic power supply.

Safety Advice: Please note recommended back box depth relies on

efficient cable routing.. Product Must Be Earthed.

Applicable Safety Standard: BS 1363-2

Commodity Code: 85366990

Declaration of Conformity









Product Features

② Ideal for charging iPad, iPhone, tablets, mobiles and cameras, supporting Qualcomm QuickCharge 3.0, and Power Delivery 3.0.

Features VARILIGHT Smart Port technology making it suitable for all types of devices.

◆ The USB port detects the device to be charged and optimises its output accordingly to achieve the fastest possible charging speed.



All information is subject to change without notice. Errors and omissions excepted. Images are for illustrative purposes only. Individual features and colours may vary. Refer to date of issue to identify latest version.

Date of Issue: 28th June 2024 © Doyle & Tratt Products Ltd, Carylls Lea, Faygate, West Sussex, RH12 4SJ, United Kingdom. All rights reserved.



Data Sheet

Product Code: XDS5UACBS

Product Description: 2-Gang 13A Single Pole Switched Socket with

1x USB A & 1x USB C Charging Ports

Range: Screwless

Finish: Brushed Steel

Product Category: Sockets with USB Charging

Insert/Knob Colour: Steel Rocker

Barcode: 5021575009101

Dimensions: 86x147x31mm

Faceplate Depth: 4mm

Net Weight: 199g

Gross Weight: 172g

Fixing Centres: 120.6mm

Depth from Mounting Face: 23.1mm

Recommended Back Box Depth: 35mm

Operating Voltage: $230v\ 50Hz$

Maximum Load Rating: 13A Socket, 20W Shared USB Charging

Maximum Current Rating: 13A

Terminal (Live) Diameter: 4.8 mm; Capacity: $4 \times 2.5 \text{mm}^2$

Terminal (Neutral) Diameter: 4.8mm; Capacity: 4 x 2.5mm²

Terminal (Earth) Diameter: 4.8 mm; Capacity: $4 \times 2.5 \text{mm}^2$

Intended Applications: Indoor Use Only. Domestic power supply.

Safety Advice: Please note recommended back box depth relies on

efficient cable routing.. Product Must Be Earthed.

Applicable Safety Standard: BS 1363-2

Commodity Code: 85366990

Declaration of Conformity









Product Features

② Ideal for charging iPad, iPhone, tablets, mobiles and cameras, supporting Qualcomm QuickCharge 3.0, and Power Delivery 3.0.

❷ Features VARILIGHT Smart Port technology making it suitable for all types of devices.

◆ The USB port detects the device to be charged and optimises its output accordingly to achieve the fastest possible charging speed.



All information is subject to change without notice. Errors and omissions excepted. Images are for illustrative purposes only. Individual features and colours may vary. Refer to date of issue to identify latest version.

Date of Issue: 28th June 2024 © Doyle & Tratt Products Ltd, Carylls Lea, Faygate, West Sussex, RH12 4SJ, United Kingdom. All rights reserved.



Data Sheet

Product Code: XDY5UACBS.MB

Product Description: 2-Gang 13A Single Pole Switched Socket with

1x USB A & 1x USB C Charging Ports

Range: Urban Screwless

Finish: Matt Black

Product Category: Sockets with USB Charging

Insert/Knob Colour: Iridium Rocker

Barcode: 5021575009163

Dimensions: 86x147x31mm

Faceplate Depth: 4mm

Net Weight: 199g

Gross Weight: 172g

Fixing Centres: 120.6mm

Depth from Mounting Face: 23.1mm

Recommended Back Box Depth: 35mm

Operating Voltage: $230v\ 50Hz$

Maximum Load Rating: 13A Socket, 20W Shared USB Charging

Maximum Current Rating: 13A

Terminal (Live) Diameter: 4.8mm; Capacity: 4 x 2.5mm²

Terminal (Neutral) Diameter: 4.8mm; Capacity: 4 x 2.5mm²

Terminal (Earth) Diameter: 4.8 mm; Capacity: $4 \times 2.5 \text{mm}^2$

Intended Applications: Indoor Use Only. Domestic power supply.

Safety Advice: Please note recommended back box depth relies on

efficient cable routing.. Product Must Be Earthed.

Applicable Safety Standard: BS 1363-2

Commodity Code: 85366990

Declaration of Conformity









Product Features

❷ Ideal for charging iPad, iPhone, tablets, mobiles and cameras, supporting Qualcomm QuickCharge 3.0, and Power Delivery 3.0.

❷ Features VARILIGHT Smart Port technology making it suitable for all types of devices.

◆ The USB port detects the device to be charged and optimises its output accordingly to achieve the fastest possible charging speed.



All information is subject to change without notice. Errors and omissions excepted. Images are for illustrative purposes only. Individual features and colours may vary. Refer to date of issue to identify latest version.

Date of Issue: 28th June 2024 © Doyle & Tratt Products Ltd, Carylls Lea, Faygate, West Sussex, RH12 4SJ, United Kingdom. All rights reserved.