

PP24-236K24050M



Key Features

Product Width: 10mm

Lm/m (up to): 2773Lm/m

Lm/W (up to): 113Lm/W

CRI: 95+

Lightsource SDCM: ≤3

Run Length (Max): 5m

Available Colours: 2300K–6000K

Warranty: 7 Years

R9 Value: >90

24V

PWM

120°  
BEAM

From  
1 Bin

>95  
CRI

HORIZ  
BEND

IP20

Mechanical Data

Bend DirectionHorizontal

Cable Length500 mm

Cable Sheath MaterialPVC

Cable Weight20 AWG

LED Chip BrandSA

Copper Foil Weight3 oz


Cut Points50 mm

LED Pitch8 mm

LEDs Per Unit12

LEDs Per Metre	240
LEDs Total	1200
PCB Type	Flexible
Self Adhesive Brand	3M
Self Adhesive Model Number	300LSE
Body Colour	White
Entry Cable Direction	End
Product Dimensions	50000x10x2 mm

Dimensions



Input

Input Voltage	24 V
---------------	------

Control

Dimming Type	PWM
--------------	-----

## Electrical Data

Constant Voltage / Constant Current	CV
Current Max · @5 Metre	4.58A
Current Max · Rated	0.916 A
Wattage Max · @1 Metre	22 W
Wattage Typ · @1 Metre	20 W
Wattage Typ · @5 Metre	100 W
Wattage Typ · @Max Run Length	100 W
Current Typ · @Max Run Length	4.165 A
Max · Run Length	5 m

## Protection

Electrical Safety Class	III
-------------------------	-----

## Photometric Data

Beam Angle	120 °
Bin Number	1
Colour Type	CCT Tunable White
CRI	95
Lumen Total	138650 Lm
Lumens Per Metre	2773 Lm/m
Lumens Per Metre (White)	2773 Lm/m
Lumens Per Watt (White)	1504 Lm/W
Lumens Per Watt (White 2)	1260 Lm/W
SDCM	< 3
Lumens Per Watt	113 Lm/W

0161 507 9249 | support@ultraleds.co.uk | www.ultraleds.co.uk | Manchester, M17 1SJ Date: 08/07/2025

Ultra LEDs have taken reasonable care to ensure that the information in this datasheet is accurate at time of publication however it should be noted that all specifications are subject to tolerance. Descriptive specifications such as colour are subjective. Ultra LEDs reserve the right to update specifications without notice. The information in the datasheet may only be relied on by customers of Ultra LEDs in accordance with applicable terms and conditions

R9 Value	94
----------	----

CCT	2300 - 6000 K
-----	---------------

#### Environment

Ingress Protection (IP)	IP20
-------------------------	------

Interior or Exterior Use	Interior
--------------------------	----------

#### Efficiency

Rated Life	50000 Hours
------------	-------------