

PRO PLUS ARCHITECTURAL SIDE VIEW PROFESSIONAL 16X17MM LED NEON FLEX, RGB COLOUR CHANGING, 24V, IP67 (£POA)

| SKU: TL-NEON-ARCPSV-RGB



ULTRA LEDs

ultraleds.co.uk

0800 088 3300

orders@ultraleds.co.uk



FEATURES & BENEFITS

- Introducing the Side View Pro Plus Neon up to IP67 rated Neon flexible lighting in 16mm x 17mm. Ideal for facades, yachts, ships, stadium lighting, outdoor feature lighting and a level of versatility and flexibility unparalleled on the market.

- High quality, high brightness

- Suitable for indoor and outdoor use

- Salt Water Resistant
Solvent Resistant
UV Resistant
Flame Resistant




TECHNICAL INFORMATION

Neon Specifications

SKU Code	TL-NEON-ARCPSV-RGB
Voltage	24V
Watts p/M	4.5W p/M
Colour Temp	Red: 620-630nm Green: 525-530nm Blue: 465-470nm
Lumens p/M	170LM
LED Chip Type	2835 Epistar
Beam Angle	120°
Max Bend Radius	60mm
CRI	90
Dimensions	16mm x 17mm
IP Rating	IP67
IK Rating	IK08
Cut Points	Every 14.66cm
Operating Temp	-20°C to +45°C
Lifespan	Up to 50000 Hours
Certification	CE, RoHs, UL, TUV, Reach
Guarantee	5 Years

Driver Requirements

1 Metre	> 6W
2 Metres	> 12W
3 Metres	> 18W
4 Metres	> 24W
5 Metres	> 36W
6 Metres	> 42W
7 Metres	> 48W
8 Metres	> 54W
9 Metres	> 62W
10 Metres	> 80W



DESCRIPTION

Introducing the Side View Pro Plus Neon up to IP68 rated Neon flexible lighting in 16mm x 17mm. Ideal for facades, yachts, ships, stadium lighting, outdoor feature lighting and a level of versatility and flexibility unparalleled on the market.

Available in Red, Green, Blue, Amber and RGB.

Our Professional Architectural Neon comes complete with a 5 Year Indoor and Outdoor Guarantee and is flame resistant, age tested against chlorine, salt, and solvents.

Built and tested to the highest standards. UL, TUV, CE & RoHs compliant and tested to rigorous mechanical and photometric standards.

The Pro Architectural range from Tagra is designed for Architects, large projects/ events and permanent installations. Fully encapsulated, it holds an IP67 ingress rating thanks to injection moulded connections and can achieve an IP68 rating if required.

A wide range of variations and accessories available with options to RAL colour match.

Ideal for Architectural and Facade lighting.

GALLERY

