



HULL VAPOR TIGHT SERIES

CORE™

SALES SHEET · 4 FT · 8 FT · HIGH BAY

Page 1 of 2

THREE FIXTURES. ONE SEALED FAMILY.

A 4 ft and 8 ft linear plus a vapor tight high bay, each with wattage and color temperature set at install. One part number covers the layout, and emergency and sensor come factory installed. Your customer stocks less; you quote faster.

Why Hull Wins the Quote:


- **9 settings per fixture.** Three wattages and three color temperatures in every Hull. Change the spec on site without a return.
- **Sealed for wet locations.** IP65, cULus wet location. Frosted, UV-stabilized, high-impact polycarbonate lens and stainless steel latches.
- **Emergency and sensor, factory installed.** 90-minute emergency battery and occupancy sensor built into the part number. 0–10V dimming.
- **Installs fast.** Surface mount kit in the box, toolless latches and a 3 ft prewired cord.
- **Rebate ready.** DLC listed. The high bay is NSF certified. IES files for every part number.
- **Handles cold and heat.** Linears run -13°F to 113°F; the high bay runs -40°F to 113°F. 5-year warranty.



4 FT LINEAR



8 FT LINEAR



SET AT INSTALL

30W–165W THREE FIXTURES	24,750 lm UP TO	150 lm/W UP TO	3CCT 3000–5000K	IP65 WET LOCATION	5-Year WARRANTY
-----------------------------------	---------------------------	--------------------------	---------------------------	-----------------------------	---------------------------

The Family · Light Output and Size:

FIXTURE	WATTAGE SETTINGS	CCT SETTINGS	LUMENS	EFFICACY	DIMENSIONS (L × W × H)	AMBIENT
HULL 4 FT	30W–40W–50W	3000K–4000K–5000K	7,000 lm	140 lm/W	47.2" × 4.7" × 3.5"	-13°F to 113°F
HULL 8 FT	60W–70W–80W	3000K–4000K–5000K	11,200 lm	140 lm/W	94.5" × 4.7" × 3.5"	-13°F to 113°F
HULL HIGH BAY	105W–135W–165W	3000K–4000K–5000K	24,750 lm	150 lm/W	47.2" × 10.4" × 4.1"	-40°F to 113°F

DLC listed lumens and efficacy at top wattage. The high bay measures 27,065 lm / 164 lm/W at its 4000K setting. Linear width measured across the latches. All fixtures 120–277V.

Construction:

- Pearl gray plastic housing
- Frosted polycarbonate lens, UV-stabilized, high-impact
- Stainless steel latches; lens releases without tools
- Surface mount kit included with every fixture

Where It Sells:

- Parking garages
- Loading docks
- Warehouses
- Coolers and cold storage
- Stairwells and corridors
- Garden centers
- Back-of-house
- Dry side of food plants

Build the Part Number:

ESLVT	+	880W	+	EM	+	S
SERIES		FIXTURE		EMERGENCY		SENSOR
FIXTURE		EMERGENCY		SENSOR		
450W 4 ft · 30W–40W–50W		(blank) None		(blank) None		
880W 8 ft · 60W–70W–80W		EM 90-minute battery		S Occupancy sensor		
HB165W High bay · 105W–135W–165W		Factory installed		Factory installed		

ESLVT450W
Hull 4 ft, 30W-40W-50W, 3CCT

ESLVT880WEM
Hull 8 ft with emergency battery

ESLVTHB165WS
Hull high bay with occupancy sensor

The Full Family · 12 Part Numbers:

PART NUMBER	FIXTURE	EMERGENCY	SENSOR
ESLVT450W	4 ft linear	—	—
ESLVT450WEM	4 ft linear	✓	—
ESLVT450WS	4 ft linear	—	✓
ESLVT450WEMS	4 ft linear	✓	✓
ESLVT880W	8 ft linear	—	—
ESLVT880WEM	8 ft linear	✓	—
ESLVT880WS	8 ft linear	—	✓
ESLVT880WEMS	8 ft linear	✓	✓
ESLVTHB165W	High bay	—	—
ESLVTHB165WEM	High bay	✓	—
ESLVTHB165WS	High bay	—	✓
ESLVTHB165WEMS	High bay	✓	✓

Every part number carries the fixture's full wattage and CCT selection. Emergency and sensor are factory installed.

Pick the Sensor by Mounting Height:

4 ft and 8 ft Up to 13 ft Built-in microwave occupancy sensor, inside the housing.	High Bay Up to 39 ft 3-pin PIR occupancy sensor, screw-in on a receptacle.
---	---

Accessories:

PART NUMBER	DESCRIPTION
ESLREM01	Sensor remote; adjusts sensitivity, hold time, daylight threshold and standby dimming
Included	Surface mount kit, every fixture

Quote It Right:

- ✓ **Lock options up front.** Emergency and sensor are factory installed and built into the part number.
- ✓ **Match the sensor to the ceiling.** 13 ft on linears; 39 ft on the high bay.
- ✓ **Set EM linears at 4000K and 5000K.** 3000K is disabled in EMG mode.
- ✓ **EM or external dimming, not both.** With emergency installed the 0–10V leads stay inside the fixture.
- ✓ **NSF job?** Quote the high bay; it carries the NSF listing.
- ✓ **Sensor job?** Add an ESLREM01 to set it up.

Certifications:

- cULus listed, wet location · IP65
- DLC listed, all three fixtures
- NSF certified, high bay
- 5-year limited warranty

Get the Layout.

Send the floor plan and mounting heights. ESL Vision returns a free photometric layout with the Hull fixture, wattage and CCT to quote. IES files and spec sheets for every part number on request.

888.493.5559