

Key Features & Benefits:

- 5CCT Field Selectable
- Compatible with 3" and 4" J Boxes
- Wet Location Rated
- 120 VAC Triac Dimmable
- T24 Compliant
- Easy Surface Mount Installation
- Optional Trim Kits*

Project:

Date:

Catalog #:

Notes:

Product Specifications:

Wattage: 14W
 Selectable Kelvin: 2700K–3000K–3500K–4000K–5000K
 Max Lumen Output: 735 Lumens
 Max Efficacy: 65 lm/W
 Voltage: 120 VAC
 Input Frequency: 50/60 Hz
 Power Factor: >0.9
 Operating Temperature: -4°F to 104°F (-20 to 40)
 Dimming: Triac 120 VAC
 Dimming Range: 10–100%
 CRI: >90
 Beam Angle: 110°
 Dimensions: L324" x W311" x 7.13" x H1.18"
 Weight (lbs): 0.75
 Finish: WH (White)
 L70 Lifetime Calculated per TM21: 50,000 hours
 Warranty: 5 Year



Ordering Guide:

ESL	TYPE	SIZE	WATTS	GEN	SELECTABLE KELVIN	VOLTAGE
ESL	DDSK	5	14W	1	2750	
(DDSK) Decorative Disk (S5) Round 5 inch (11W) 11 Watts - 5" (S7) Round 7 inch (14W) 14 Watts - 7" (S9) Round 9 inch (20W) 20 Watts - 9" (S11) Round 11 inch (25W) 25 Watts - 11" (1) 1st Gen (2750) 2700K–3000K–3500K–4000K–5000K (Blank) 120 V						

