



INTELLISENSE™ BACKLIT PANELS

ESL-ISS-620-24-3050W-3550K

Key Features & Benefits:

- IntelliSense™ Sensor Enabled
- Wattage and Kelvin Selectable
- Slim Design for Multiple Applications
- 1–10V Dimming
- Back Lit for Uniform Lighting

Project: _____

Date: _____

Catalog #: _____

Notes: _____

Product Specifications:

Selectable Kelvin: 3500K–4000K–5000K
Max Lumen Output: 5,000 Lumens
Max Efficacy: 125 lm/W
Voltage: 120–277 VAC
Input Frequency: 50/60 Hz
Power Factor: >0.9
THD: 80
Dimensions: L47.76" x W23.74" x H1.42"
Weight (lbs): 8.02
Finish: WH (White)
L70 Lifetime Calculated per TM21: L70 > 100,000 hrs
Warranty: 5 Year



Ordering Guide:

ESL	TYPE	SIZE	SELECTABLE WATTAGE	KELVIN	SELECTABLE KELVIN
ESL	ISS-620	24	3050W	3550K	3550
	(ISS-620) IntelliSense™ Series Backlit Panel	(22) 2x2 (14) 1x4 (24) 2x4	(2040W) 20W–30W–40W (3050W) 30W–40W–50W		(3550K) 3500K–4000K–5000K

