

## Key Features & Benefits:

- Kelvin and Wattage Selectable
- Self-Contained LED and Lens for Easy Install
- 0–10V Continuous Dimming
- 3/4" Knockouts on Both Sides for Continuous-Run Mounting

Project: \_\_\_\_\_

Date: \_\_\_\_\_

Catalog #: \_\_\_\_\_

Notes: \_\_\_\_\_

## Product Specifications:

Selectable Wattage: 15W–20W–25W  
 Selectable Kelvin: 3500K–4000K–5000K  
 Max Lumen Output: 3,750 Lumens  
 Max Efficacy: 150 lm/W  
 Voltage: 120–277 VAC  
 Input Frequency: 50/60 Hz  
 Operating Temperature: -4°F to 104°F (-20 to 40 )  
 Dimming: 0–10V 12V AUX  
 Dimming Range: 0%-100%  
 Dim to Off: true  
 CRI: >80  
 Beam Angle: 110°  
 Dimensions: L22.32" x W2.83" x H2.52"  
 Weight (lbs): 2.09  
 Finish: WH (White)  
 L70 Lifetime Calculated per TM21: 100,000 hours  
 Warranty: 5 Year



## Ordering Guide:

ESL	TYPE	SIZE	SELECTABLE WATTAGE	GEN	SELECTABLE KELVIN
ESL	CSS-801	2	1525W	2	3550
	(CSS-801) Contractor Series Selectable Strip	(2) 2Foot (4) 4Foot (8) 8Foot	(1525W) 15W–20W–25W - 2 Ft (2030W) 20W–30W–40W - 4 Ft (3055W) 30W–40W–55W - 4 Ft (70100W) 70W–85W–100W - 8 Ft	(2) 2nd Gen	(3550K) 3500K–4000K–5000K



