



LED AMBER MUR SERIES

ESL-MUR-120W-3-590NM

Key Features & Benefits:

- Reduces Light Pollution and Adverse Effects on Wildlife
- Utilizes Existing Fixtures for Fast and Cost Effective Installation
- Indoor and Outdoor Applications:
 - Beach Front & Waterways
 - Airports
 - Commercial & Retail
 - Parking Lots & Buildings
 - Food & Beverage Production
- 10 Year Warranty
- Optimized Pin Array Heatsink
- Overheat Shutdown
- L70 Lifetime >100,000 Hours
- Intelligent Thermal Control
- Compatible with Networked Lighting Control Qualified Systems

Product Specifications:

Wattage: 120W
Kelvin: 590NM
Max Lumen Output: 9,720 Lumens
Max Efficacy: 81 lm/W
Voltage: 120–277 VAC
Input Frequency: 50/60 Hz
Surge Protection: Yes
Operating Temperature: -40°F to 176°F (-40°C to 80°C)
Dimming: 0–10V 12V AUX
Dimming Range: 0-100%
Dim to Off: true
CRI: >75
Dimensions: L6.81" x W4.88" x H2.6"
Weight (lbs): 1.05
Finish: WH (White)
L70 Lifetime Calculated per TM21: 100,000 hours
Warranty: 10 Year

Project:

Date:

Catalog #:

Notes:



Ordering Guide:

ESL	TYPE	WATTS	GEN	KELVIN	VOLTAGE
ESL	MUR	120W	3	590N	
	(MUR) MultiUse Retrofit	(105W) 105 Watts (120W) 120 Watts (150W) 150 Watts (200W) 200 Watts		(590NM) Amber	(Blank) 120 V (HV) 277–480 V

