

Key Features & Benefits:

- Kelvin and Wattage Selectable
- Self-Contained LED and Lens for Easy Install
- 0–10V Continuous Dimming
- 3/4" Knockouts on Both Sides for Continuous-Run Mounting

Project: _____

Date: _____

Catalog #: _____

Notes: _____

Product Specifications:

Selectable Wattage: 70W–85W–100W
 Selectable Kelvin: 3500K–4000K–5000K
 Max Lumen Output: 15,000 Lumens
 Max Efficacy: 150 lm/W
 Voltage: 120–277 VAC
 Input Frequency: 50/60 Hz
 Operating Temperature: -4°F to 104°F (-20 to 40)
 Dimming: 0–10V 12V AUX
 Dimming Range: 0%-100%
 Dim to Off: true
 CRI: >80
 Beam Angle: 110°
 Dimensions: L94.17" x W2.83" x H2.52"
 Weight (lbs): 8.6
 Finish: WH (White)
 L70 Lifetime Calculated per TM21: 100,000 hours
 Warranty: 5 Year



Ordering Guide:

ESL	TYPE	SIZE	SELECTABLE WATTAGE	GEN	SELECTABLE KELVIN
ESL	CSS-801	8	70100W	2	3550
(CSS-801) Contractor Series Selectable Strip (2) 2Foot (4) 4Foot (8) 8Foot (1525W) 15W–20W–25W - 2 Ft (2030W) 20W–30W–40W - 4 Ft (3055W) 30W–40W–55W - 4 Ft (70100W) 70W–85W–100W - 8 Ft (2) 2nd Gen (3550K) 3500K–4000K–5000K					



