



## Sensor Flushometer

### EBV500A-CP

#### Product description

Polished Chrome Finish, Fixture Connection Top Spud, Single Flush, Battery, Infrared, Exposed Sensor Urinal/Water Closet Retrofit Flushometer.

#### Compliances & Certifications



(ADA Compliant, BAA Compliant, BREEAM Water Credit, cUPC Certified, Green Globes Water, IAPMO)

#### Code 3325500

#### Finish

-  Polished Chrome (CP)

#### Downloads

-  [EBV-500\\_550-A Installation Instructions.pdf](#)
-  [EBV500-EBV550 Repair and Maintenance Guide.pdf](#)
-  [Retrofits Brochure.pdf](#)
-  [Additional Downloads](#)

#### Videos

-  [Sloan - Company Overview](#)

---

## Details

- Finish: Polished Chrome (CP)
- Power Type: Battery
- Valve: Diaphragm
- Piston
- Fixture Type: Urinal/Water Closet
- Fixture Connection: Top Spud

---

## Features

- 72-Hour Sentinel Flush
- Battery powered
- Estimated 3 year battery life
- True Mechanical Override for manual flush

---

## Electrical specifications

- Arming Delay: 1 - 3 seconds
- Control Circuit:
  - 6 VDC Input
  - 72 Hour Sentinel Flush
  - Solid State
- Sensor Range: 22"-42" (559 - 1067mm)

---

## Valve Operating Pressure (Flowing)

15-80 psi (103 - 552 kPa). Specific fixtures may require greater minimum flowing pressure - consult manufacturer requirements.

---

## Warranty

[View Warranty Information](#)

---

## Notes

All information contained within this document subject to change without notice.

Looking for other variations of the EBV500A product? [View the general spec sheet with all options.](#)

[Find a compatible urinal](#) for this flushometer.

[Find a compatible water closet](#) for this flushometer.

