Printing date 06.08.2008

Revision: 06.08.2008

1 Identification of the substance/preparation and of the company/undertaking

· Product details

- · Trade name: Lubricant Oil 100 ml
- · Application of the substance / the preparation Lubricating oil

• Manufacturer/Supplier: Aerochemica GmbH Hooghe Weg 35 47906 Kempen Tel.: 02152/141613 Fax: 02152/50849

· Further information obtainable from: Abteilung Produktsicherheit

 Information in case of emergency: Giftinformationszentrum Nord der Länder Bremen, Hamburg, Niedersachsen und Schleswig-Holstein (GIZ Nord), Georg August Universität Göttingen, Zentrum Pharmakologie und Toxikologie, Robert Koch Straße 40, 37075 Göttingen Tel.: 0551/192 40 Fax: 0551/383 1881

2 Hazards identification

· Hazard description: Not applicable.

· Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

Warning! Pressurized container.

R 53 May cause long-term adverse effects in the aquatic environment.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Keep out of the reach of children

· Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

· GHS label elements

Danger

2.2/1 - Extremely flammable gas.

2.3/1 - Extremely flammable aerosol.

4.1/4 - May cause long lasting harmful effects to aquatic life. **Prevention**:

· Prevention:

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid release to the environment.

· Response:

Leaking gas fire: Do not extinguish, unless leak can be stopped safely. Eliminate all ignition sources if safe to do so.

· Storage:

Store in a well-ventilated place.

Protect from sunlight. Do no expose to temperatures exceeding 50°C/122°F.

· Disposal:

Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 2)

GR

Printing date 06.08.2008

Revision: 06.08.2008

Trade name: Lubricant Oil 100 ml

(Contd. of page 1)

3 Composition/information on ingredients

- · Chemical characterization
- Description: Mixture of substances listed below with nonhazardous additions.

 Dangerous compone 	ents:		
CAS: 90622-58-5	Isoparaffine	🗙 Xn; R 53-65-66	25-50%
		Danger: 🚸 3.10/1	
		Warning: 2.6/4, 4.1.C/4	
CAS: 124-38-9	carbon dioxide	Warning: $\bigotimes 2.5/L$	2.5-10%
EINECS: 204-696-9		ũ V	

• Additional information: For the wording of the listed risk phrases refer to section 16.

4 First aid measures

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- *After skin contact: Generally the product does not irritate the skin.*
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.

5 Fire-fighting measures

- · Suitable extinguishing agents:
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · Protective equipment: No special measures required.

6 Accidental release measures

- · Person-related safety precautions: Not required.
- Measures for environmental protection:
- Do not allow product to reach sewage system or any water course.
- Inform respective authorities in case of seepage into water course or sewage system.
- Do not allow to enter sewers/ surface or ground water.
- · Measures for cleaning/collecting: Ensure adequate ventilation.

7 Handling and storage

- · Handling:
- Information for safe handling: Ensure good ventilation/exhaustion at the workplace.
- · Information about fire and explosion protection:

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

Do not spray onto a naked flame or any incandescent material.

- · Storage:
- Requirements to be met by storerooms and receptacles:
- Observe official regulations on storing packagings with pressurized containers.
- Information about storage in one common storage facility: Not required.
- $\cdot \textit{Further information about storage conditions: None.}$

8 Exposure controls/personal protection

• Additional information about design of technical facilities: No further data; see item 7.

(Contd. on page 3)

GB

Printing date 06.08.2008

Revision: 06.08.2008

Trade name: Lubricant Oil 100 ml

(Contd.	of	page	2)

• Ingredients with limit values that require monitoring at the workplace: 124-38-9 carbon dioxide

WEL Short-term value: 27400 mg/m³, 15000 ppm Long-term value: 9150 mg/m³, 5000 ppm

• Additional information: The lists valid during the making were used as basis.

· Personal protective equipment:

· General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

• Protection of hands:



Protective gloves

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection: Not required.

General Information		
Form:	Aerosol	
Colour:	According to product specification	
Odour:	Characteristic	
Change in condition		
Melting point/Melting range:	Undetermined.	
Boiling point/Boiling range:	180°C	
Flash point:	> 55°C	
Ignition temperature:	265°C	
Self-igniting:	Product is not selfigniting.	
Danger of explosion:	Product does not present an explosion hazard.	
Vapour pressure at 20°C:	ca. 6000 hPa	
Density at 20°C:	0.857 g/cm ³	
Solubility in / Miscibility with		
water:	Not miscible or difficult to mix.	
Solvent content:		
Organic solvents:	0.0 %	
VÕC (EC)	41.31 %	

(Contd. on page 4)

Printing date 06.08.2008

Revision: 06.08.2008

Trade name: Lubricant Oil 100 ml

(Contd. of page 3)

10 Stability and reactivity

- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Dangerous reactions No dangerous reactions known.
- · Dangerous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Acute toxicity:
- · Primary irritant effect:
- · on the skin: No irritant effect.
- on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.

12 Ecological information

· General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

13 Disposal considerations

- · Product:
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.


2 5F Gases.

1950

2.1

14 Transport information

· Land transport ADR/RID (cross-border)





· IMDG Class:	2.1
· UN Number:	1950
· Label	2.1
• Packaging group:	-

(Contd. on page 5)

GR

Printing date 06.08.2008

Revision: 06.08.2008

Trade name: Lubricant Oil 100 ml

• EMS Number:	F- D , S - U	
· · · · · · F · · · · · · · · ·	No	
· Proper shipping nam	: AEROSOLS	
· Air transport ICAO-1	I and IATA-DGR:	
2		
· ICAO/IATA Class:	2.1	
· UN/ID Number:	1950	
· Label	2.1	
· Packaging group:	-	
	: AEROSOLS, flammable	
r roper snipping nam	: AEKOSOLS, jiammable	

15 Regulatory information

· Labelling according to EU guidelines:

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

· Risk phrases:

53 May cause long-term adverse effects in the aquatic environment.

· Safety phrases:

- 23 Do not breathe gas/fumes/vapour/spray (appropriate wording to be specified by the manufacturer).
- 24 Avoid contact with skin.
- 29/56 Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.
- 60 This material and its container must be disposed of as hazardous waste.

· Special labelling of certain preparations:

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Keep out of the reach of children

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant R-phrases

53 May cause long-term adverse effects in the aquatic environment.

65 Harmful: may cause lung damage if swallowed.

66 Repeated exposure may cause skin dryness or cracking.

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises Dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Reglement internationale concernent le transport des merchandises dangereuses par chemin de fer (Regulations Concerning the

- International Transport of Dangerous Goods by Rail) IMDG: International Maritime Code for Dangerous Goods
- IMDG: International Maritime Coae for Danger IATA: International Air Transport Association
- IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)
- ICAO: International Civil Aviation Organization
- ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)
- GHS: Globally Harmonized System of Classification and Labelling of Chemicals