
GPS/GLONASS/GALILEO ANTENNA

- **GNSS active Antenna**
- **GPS, Glonass and Galileo**
- **32 dB Gain**
- **3 – 5 V**
- **Wide temperature range**

ADA-DS56 is a GPS/ GLONASS combined antenna. It's an active antenna design to operate at the frequency of

- GPS L1 1575.42MHz.
- GLONASS L1 $1602 + (n * 0,5625)$ MHz.
- GALILEO L1 1575.42MHz.

ADA-DS56 is optimized to receive right-hand-circularly-polarized signals and have LNA designed in. The antenna can be fixed by an optional mounting base.



Specification

Category	Overall performance
Frequency	1572 - 1615 MHz (CF: 1590 MHz)
Polarization	R.H.C.P.
Peak Gain	4 dBic min / 1575 MHz 4 dBic min / 1602 - 1615 MHz
Output Impedance	50 Ω
Power Handling	1 W
Amplifier Gain	Typ. 32 dB
Noise figure	1.5 dB
VSWR	2.0 Max
Supply Voltage	3 – 5 VDC
Current consumption	18 \pm 3 mA
Operating temperature	-40 – +85 ° C
Storage temperature	-50 – +95 ° C

Ordering codes

TYPE	Description	Comment
ADA-DS56	GPS, GLONASS and GALILEO antenna	1575 - 1615 MHz antenna

For the latest updates, visit our Web site: www.adactus.se

Disclaimer

Information furnished is believed to be accurate and reliable. However, Adactus assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use.

Adactus reserves the right to make changes without further notice to any product herein to improve reliability, function or design. Adactus does not assume any liability arising out of the application or use of any product described herein.

This publication supersedes and replaces all information previously supplied.

Adactus products are not authorized as critical components in life support devices or systems.