

K Mounts

3/4" Hole Rooftop Mounts for 800 MHz "Male-Female Contact" Antennas



STANDARD CONFIGURATION

Model	Length of Coax	Coax	Connector*
K166M	17'	RG-58/U	Mini-UHF crimped
K166MTT	25'	RG-58/U	Mini-UHF crimped
K166T	17'	RG-58/U	TNC male crimped
KD166T	17'	Pro-Flex™ Plus 195	TNC male crimped
KE166U	17'	Pro-Flex™ Plus 195	FME Female
KE166UMT	17'	Pro-Flex™ Plus 195	FME Female**



K166

3/8" Snap-In Rooftop Mount for Quarter Wave Antennas (sold in packs of 5 units each)

STANDARD CONFIGURATION

Model	Length of Coax	Coax	Connector
K44//5PCK	N/A	Sold Separately	None




K44/5PCK

(B)MBM Series

Black or chrome, 1-1/8"-18 thread; mirror bracket mount

STANDARD CONFIGURATION

Model***	Length of Coax	Coax	Connector*	Type
(B)MBM-NC	17'	RG-58A/U	None	N/A
MBMC-NC	17'	RG-58/U	None	N/A
(B)MBM	17'	RG-58A/U	PL259	Solder
(B)MBMC	17'	RG-58/U	TNC	Crimp
(B)MBMPL	17'	RG-58/U	Mini-UHF	Crimp



BMBM MOUNTS

* Connectors are shipped loose. Connectors may be attached upon request for an additional charge

** Plus MINI-UHF to FME and TNC to FME adapter loose

*** (B) prefix indicates black option