

# Shireoak

## 26mm



Certified  
Company



Chlorine  
Resistant



Made in  
Belgium



10 Year  
Warranty



Eco  
Friendly



Pet  
Friendly



Child  
Friendly



UV  
Stability



Heavy  
Usage

## TECHNICAL SPECIFICATION

Fibre	65% PE / 35% PP straight / curled
Fibre Shape	Xtra Spine Technology (XST)
Pile height	ca. 26 mm
Stitches	ca. 21 st/10 cm
Production	Tufting
Gauge	3/8"
Tufts	ca. 22050 / m <sup>2</sup>
Pile weight	ca. 900 gr / m <sup>2</sup>
Total weight	ca. 1870 gr / m <sup>2</sup>
Tuft cloth	Polypropylene woven, ca. 170 gr / m <sup>2</sup>
Backing	Pre coat, ca. 800 gr / m <sup>2</sup>
Roll width	200 cm / 400 cm
Roll length	± 35 m
UV Stability	>3.000 hours UV-A   6,000 hours XENON
Light fastness	Scale 7 (DIN 54004)
Chlore resistance	4 – 5 (DIN 54019)
Resistance to sea water	4 – 5 (DIN 54007)

**Address** - Unit 1, West Way, Cotes Park Ind Est, Alfreton, Derby, DE55 4QJ

[www.perma-lawn.co.uk](http://www.perma-lawn.co.uk)



01773 608 808



[info@perma-lawn.co.uk](mailto:info@perma-lawn.co.uk)