

# SALONI

<b>MODEL:</b> Team Multi 19x57		
<b>BRAND:</b> SALONI	<b>CODE:</b> ZL6395	<b>EDITION:</b> 1
<b>CLASSIFICATION (UNE-EN-14411):</b> Grupo BIIa. Anexo J		<b>DECLARATION OF BENEFITS:</b> 01DP
STANDARD	CHARACTERISTICS	TEST RESULT
UNE-EN ISO 10545-3	Water absorption	3,0% < E < 6,0%
UNE-EN ISO 10545-4	Breaking strength (N)	1800
UNE-EN ISO 10545-4	Modulus of rupture (N/mm <sup>2</sup> )	35
UNE-EN ISO 10545-6	Resistance to deep abrasion (mm <sup>3</sup> )	
UNE-EN ISO 10545-7	Abrasion resistance	
	Class	4
	Stage	2100 Rev.
UNE-EN ISO 10545-9	Thermal shock resistance	
UNE-EN ISO 10545-11	Resistance to crazing	O.k.
UNE-EN ISO 10545-12	Frost Resistance	
UNE-EN ISO 10545-13	Chemical Resistance	
	Household Chemicals	A
	Swimming pool salts	A
	Citric Acid	LA
	Lactic Acid	HA
	Hydrochloric Acid low concentrations	LA
	Hydrochloric Acid high concentrations	HA
	Potassium Hydroxide low concentrations	LA
Potassium Hydroxide high concentrations	HA	
UNE-EN ISO 10545-14	Resistance to staining	
	Fe2O3 / Cr2O3	Class Mín. 3
	Iodine / alcohol solution	Class Mín. 3
	Light oil	Class Mín. 3
UNE-41901:2017 EX	Slip Resistance	
<b>Dimension (mm)</b>	191,0x572,0	<b>Thickness (mm)</b> 9,5
<b>Classification according to Saloni quality:</b>		D

This document is for commercial and informational use. Saloni reserves the right to modify or eliminate any information contained in it.  
In case of doubt, please verify the data of this technical sheet with the factory.

Printing date: 25/02/2020



Cerámica Saloni S.A.U.  
[www.saloni.com](http://www.saloni.com)

## DECLARACIÓN DE PRESTACIONES

Nº. 01DP

**1.- Código del producto tipo. (Identification code of the product type).**

Baldosa cerámica prensada en seco, con absorción de agua  $3% < Eb \leq 6 \%$   
(Ceramic tiles, dust pressed with water absorption  $3% < Eb \leq 6 \%$ )

**2.- Usos previstos. (Intended use(s)).**

Para suelos interiores y paredes interiores  
(For internal floor and wall)

**3.- Nombre y dirección del fabricante: (Name and contact address of the manufacturer).**

Cerámica SALONI, SAU  
Ctra. Alcora, Km. 17  
12130 San Juan de Moró, Spain  
www.saloni.com

**4.- Sistema de evaluación y verificación de la constancia de prestaciones. (System(s) of assessment and verification of constancy of performance).**

Sistema 4 (System 4).

**5.- Organismo notificado. (Notified laboratory, if relevant).**

No aplica

**6.- Prestaciones declaradas. (Declared performances).**

Características esenciales (Essential characteristics)	Prestaciones (Performance)	Especificación técnica armonizada (Harmonised technical specification)
<b>Reacción al fuego</b> (Reaction to fire)	A1 <sub>FL</sub> / A1	EN14411:2012
<b>Emisión de sustancias peligrosas:</b> Cadmio (Cadmium) Plomo (Lead)	PND PND	
<b>Fuerza de rotura</b> (Breaking strength)	>1100 N	
<b>Deslizamiento</b> (Slipperiness)	PND	
<b>Propiedades táctiles</b> (Tactility)	PND	
<b>Adhesión para: Adhesivo cementoso tipo C1</b> (Bond strength/adhesión for: cementitious adhesive type C1)	>0,5 N/mm <sup>2</sup>	
<b>Durabilidad para: usos interiores</b> (Durability for internal use)	Cumple (Pass)	

Las prestaciones del producto identificado en el punto 1 son conformes con las prestaciones declaradas en el punto 6. (The performance of the product identified in point 1 is in conformity with the declared performances in point 6)

La presente declaración de prestaciones se emite bajo la única responsabilidad del fabricante indicado en el punto 3. (The declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3)

Firmado en nombre del fabricante por (Signed for and on behalf of the manufacturer by):



J. Pablo Sansano Ten  
Jefe Dpto. Calidad

San Juan de Moró. 01.07.2013