

INSTALLATION NOTES & GUIDELINES FOR MAC OS X

Before Installation

1. Check and take note of your OS version by clicking on the top left menu "apple" -> About this Mac - or running Utilities -> System Information.app -
2. Two kinds of installation packages are available, one kind for full installation, and one for upgrade only. If you already have a fully **functional** version of the Cressi Pc Interface application on your system, you only need to download an "upgrade" installation package. If not, you'll have to use a "full" installation package instead
3. Download the dmg file that matches your needs (upgrade or full) and your OS X version. WARNING: a wrong choice may result in a nonfunctional installation.
4. Make sure that your system accept applications downloaded from "anywhere" (check under "apple" -> System Preferences -> Security and Privacy -> General)

Installation steps for Mac OS X 10.7 to 10.9

5. Disconnect the USB Cressi Interface, as well as other similar USB devices (there's no need to disconnect external USB drives or other storage media)
6. The dmg file contains the installation package: if your settings allow file extensions, you'll see it as ".mpkg" file; the associated icon resembles a cardboard box.
7. Double click on the package: the installation process will start.
8. Choose "standard install" when asked for installation type
9. You may get a system message referring to "lipo command" and offering the option to install Xcode-related packages: choose not to install them, and disregard the message
10. After installation, reboot the system
11. After rebooting, the USB interface can be reconnected

Installation steps for Mac OS X 10.10 "Yosemite" and 10.11 "El Capitan"

5. Disconnect the USB Cressi Interface, as well as other similar USB devices (there's no need to disconnect external USB drives or other storage media)
6. The dmg file contains two installation packages: if your settings allow file extensions, you'll see them as ".mpkg" files; the associated icons resemble a cardboard box. Observe the package names:

"1_CressiPcInterface_1_3_0_**Pre**_Installation" is the "PREinstaller" and it has to be installed first; the 2nd, either "2_CressiPcInterface_1_3_0_Full_Installation" or "2_CressiPcInterface_1_3_0_Upgrade", is the "real installer" and it has to be executed after the PREinstaller

7. So, the sequence you have to follow is:
run the "PREinstaller";
reboot your system;
run the (upgrade or full) "installer";
reboot your system again.

WARNING: using the packages out of sequence will result in a nonfunctional installation.

8. Double click on the package of choice: the installation process will start (N. B. the PREinstaller is very quick to complete whereas the full/upgrade installer will take longer).
9. Choose "standard install" when asked for installation type
10. You may get a system message referring to "lipo command", and offering the option to install Xcode-related packages: choose not to install them, and disregard the message
11. After installation, reboot the system
12. After having completed both the PREinstallation and the full/upgrade installation, the USB interface can be reconnected

NOTES

- Application and data are kept local to the Home dir of the user who performed the installation
- Old application data (logbook database, settings) that may be present from previous installations, are preserved as much as possible