

DIN 976-1

Barra filettata tipo A, estremità filettata grezza (RL) secondo DIN EN ISO 4753

Stud bolt type A, with As-rolled (RL) type thread end as in DIN EN ISO 4753


Disponibile/Available A4 

A2 



u (filetto incompleto): $2 P$ max.
 u (incomplete thread): $2 P$ max.

As-rolled end (RL)



Thread size, d tolerance class 6g			M2	M2,5	M3	(M3,5)	M4	M5	M6	M8	M10	M12							
			-	-	-	-	-	-	-	M8x1	M10x1,25	M12x1,25							
			-	-	-	-	-	-	-	-	M10x1	M12x1,5							
l_t			Mechanical properties																
Nom. Size			$3 \text{ mm} \leq d \leq 24 \text{ mm}$																
min.			A2-70 / A4-70																
max.			1000	995,5	1004,5														
			2000	1992,5	2007,5	ON REQUEST	ON REQUEST	ON REQUEST	ON REQUEST	ON REQUEST									
			3000	2989,5	3010,5	ON REQUEST	ON REQUEST	ON REQUEST	ON REQUEST	ON REQUEST									
Thread size, d tolerance class 6g			(M14)	M16	(M18)	M20	(M22)	M24	(M27)	M30	(M33)	M36							
			(M14X1,5)	M16X1,5	(M18X1,5)	M20X1,5	(M22X1,5)	M24X2	(M27X2)	M30X2	(M33X2)	M36X3							
			-	-	-	-	-	-	-	-	-	-							
l_t			Mechanical properties																
Nom. Size			$3 \text{ mm} \leq d \leq 24 \text{ mm}$																
min.			A2-70 / A4-70																
max.			1000	995,5	1004,5														
			2000	1992,5	2007,5									ON REQUEST	ON REQUEST				
			3000	2989,5	3010,5														ON REQUEST
Thread size, d tolerance class 6g			(M39)	M42	(M45)	M48	(M52)	M56	(M60)	M64	(M68)	-							
			(M39X3)	M42X3	(M45X3)	M48X3	(M52X3)	M56X4	(M60X4)	M64X4	(M68X4)	M72X6							
			-	-	-	-	-	-	-	-	-	-							
l_t			Mechanical properties																
Nom. Size			$3 \text{ mm} \leq d \leq 24 \text{ mm}$																
min.			A2-70 / A4-70																
max.			1000	995,5	1004,5									ON REQUEST	ON REQUEST	ON REQUEST	ON REQUEST	ON REQUEST	ON REQUEST
			2000	1992,5	2007,5	ON REQUEST	ON REQUEST	ON REQUEST	ON REQUEST	ON REQUEST	ON REQUEST	ON REQUEST	ON REQUEST	ON REQUEST	ON REQUEST	ON REQUEST	ON REQUEST	ON REQUEST	
			3000	2989,5	3010,5	ON REQUEST	ON REQUEST	ON REQUEST	ON REQUEST	ON REQUEST	ON REQUEST	ON REQUEST	ON REQUEST	ON REQUEST	ON REQUEST	ON REQUEST	ON REQUEST	ON REQUEST	

Evitare i diametri tra parentesi se possibile/ Bracketed sizes should be avoided if possible.

last edit 30/03/2020

DRAWING N. 1147