

SBH-D / SBH-G

HOT WATER HIGH PRESSURE CLEANER - ELECTRIC POWERED

The SBH hot-water high-pressure cleaner is particularly suitable for a wide range of cleaning jobs, because it offers the choice of cold- or hot-water cleaning. This high-pressure cleaner is produced in 2 versions, i.e. with a diesel boiler (= model D) or a gas boiler (= model G).

A stationary unit is the most obvious solution to clean using hot water in one or more rooms, without the need to move the high pressure cleaner.



HIGH-QUALITY MATERIALS
with stainless steel cover

OPERATING PANEL
easy to use:

- ON/OFF
- Boiler switch
- Temperature adjustment
- Hour counter


STANDARD ACCESSORIES :



Single stainless steel lance with high pressure nozzle and rotating quick coupling
code : 1.216.729.xxxx



High pressure gun with swivel
code : 1.211.525



Radial high pressure pump with 3 ceramic plungers and stainless steel valves



Flexible engine/pump coupling

TECHNICAL SPECIFICATIONS :

- Automatic start/stop system with 30 s shut-down-delay
- Motor at low speed (1450 rpm)
- Stainless steel cover for the engine/pump section
- Diesel boiler (model D)
- Gas boiler (model G)
- Flexible engine/pump coupling
- Radial high pressure pump with 3 ceramic plungers and stainless steel valves
- Pressure gauge
- Coarse particle filter
- Hour counter
- Detergent suction with dosing valve

Note: Monophase machines work as standard at 1 x 230 V- 50 Hz. 3-phase machines work as standard at 3 x 400 V- 50 Hz. Other versions on request.

Note: the machine is not equipped with high pressure hose

MODELS :

SBH-D												
TYPE												
	bar	l/h	°C	kW	m	l	l	mm	kg			
1.119.100 150/15 D	30 - 150	180 - 900	30 - 150	4,0 (3 x 400V- 50HZ- 9A)	5	27	10	820x920x1040	163	05		
1.119.300 200/15 D	30 - 200	180 - 900	30 - 150	5,5 (3 x 400V- 50 Hz- 12A)	5	27	10	820x920x1040	180	04		

SBH-G												
TYPE												
	bar	l/h	°C	kW	m	l	l	mm	kg			
1.119.125 150/15 G	30 - 150	180 - 900	30 - 95	4,0 (3 x 400V- 50 Hz- 9A)	5	-	10	820x920x1040	163	05		
1.119.325 200/15 G	30 - 200	180 - 900	30 - 95	5,5 (3 x 400V- 50 Hz- 12A)	5	-	10	820x920x1040	163	04		