

EVERFLEX 175 UNIVERSAL ACRYLIC SEALANT

| Colour | Product Code | Pack Size | Box Qty |
|--------|--------------|------------|---------|
| White | 175WE | C3 | 25 |
| | FP175WE6 | 600ml Foil | 12 |
| Brown | 175BN | C3 | 25 |
| Grey | FP175GY6 | 600ml foil | 12 |

Product Description

EVERFLEX 175 UNIVERSAL ACRYLIC SEALANT is an acrylic Sealant, suitable for internal and external use that provides a permanently flexible long lasting seal that adheres to virtually all materials. Contains anti-fungal agent to prevent mould growth in areas of high humidity, and can be overpainted.

Benefits

- Permanently flexible
- Adheres to most surfaces.
- Mould resistant.
- Overpaintable.
- Easy clean up

Areas For Use

- Internal and external sealing around timber and metal window and door frames.
- PVCu profile, trim and cladding.
- Internal sealing around PVCu window and door frames.
- Sealing cracks and gaps in brickwork, stone and concrete.
- An adhesive for bonding polystyrene coving and tiles.
- An adhesive for bonding cork tiles and wood block flooring.
- Gap and crack filler prior to decorating.
- Sealing around baths, and basins.

Limitations

- Protect from water for a minimum of 24 hours after application. Note that damp or humid conditions will significantly extend the cure time. Do not expose to water until fully cured. If a quicker cure is required, use GENERAL PURPOSE SILICONE (6 hour cure).
- Not for use in conjunction with bitumen or asphalt.
- Do not attempt to abrade when cured.
- Do not use around shower trays. Use GENERAL PURPOSE SILICONE for greater movement capabilities
- Do not overpaint until a surface skin has formed. Overpainting is not necessary.
- Note: this product is a flexible. Certain poor quality paints (especially certain vinyl matt) have very little movement in the dry film. It is possible for the dry paint film to crack if movement is excessive.
- Not for use externally when rain is imminent (within 6 hours at 20°C, 12 hrs at 10°C.). Note that low temperatures will significantly retard the cure, skinning time.

The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired. Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product. Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions. The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.