



**Building & DIY Products You Can Trust**

Site 41, Knowsthorpe Way,

Cross Green Industrial Estate, Leeds, LS9 0SW

Telephone: +44 (0) 113 240 3456 Sales: +44 (0) 113 240 2424

Fax: +44 (0) 113 240 0024

e-mail: [info@everbuild.co.uk](mailto:info@everbuild.co.uk)

website: [www.everbuild.co.uk](http://www.everbuild.co.uk)

## CONSTRUCTION PRODUCTS REGULATION

### DECLARATION OF PERFORMANCE

**No: 825/1-CPR/ 2014**

Substrate: Mortar M2

Primer: No primer

|  |   |
|--|---|
| 1. Identification Code                                     | <b>Everbuild 825 Silicone Sealant;</b><br><b>Codes: 825 / FP825</b>   |
| 2. Type, Batch and/or Serial Number                        | <b>- For batch number - see packaging</b>   |
| 3. Intended use  | <b>Sealant for non-structural use in joints in buildings and pedestrian walkways Part 1: Sealants for Façade elements</b> |
| 4. Manufacturer  | <b>Everbuild Building Products Ltd, Site 41, Cross Green Industrial Estate, Knowsthorpe Way, Leeds, LS9 0SW</b>           |
| 5. Authorised Representative                               | <b>Not Applicable</b>   |
| 6. Assessment and Verification of Constancy of Performance | <b>System 3</b>   |
| 7. Notified Body and Tasks                                 | <b>Ginger CEBTP Notified Body No. 00074</b>   |
| 8. European Technical Assessment                           | <b>Not Applicable</b>   |
| 9. Declared Performance                                    | <b>TO EN15651-1 (2012)</b>  |
| Type   | <b>F EXT-INT-CC</b>   |
| Classification   | <b>F25LM</b>  |
| Reaction to Fire   | <b>Class E</b>  |



**Building & DIY Products You Can Trust**

Site 41, Knowsthorpe Way,

Cross Green Industrial Estate, Leeds, LS9 0SW

Telephone: +44 (0) 113 240 3456 Sales: +44 (0) 113 240 2424

Fax: +44 (0) 113 240 0024

e-mail: [info@everbuild.co.uk](mailto:info@everbuild.co.uk)

website: [www.everbuild.co.uk](http://www.everbuild.co.uk)

|   |          |
|---|----------|
| Loss of Volume ISO10563   | ≤10%     |
| Resistance to flow ISO7390  | ≤3 mm    |
| Adhesion/cohesion properties at maintained extension after water immersion (23°C) ISO 10590 | NF       |
| Adhesion/cohesion properties (-30°C)  | ≤0.9 MPa |
| Durability ISO 8340, ISO 9047 and ISO 10590   | Pass     |

Substrate: Glass

Primer: No primer

|  |  |
|--|--|
| 1. Identification Code                                     | <b>Everbuild 825 Silicone Sealant;</b><br><b>Codes:</b>  |
| 2. Type, Batch and/or Serial Number                        | - For batch number - see packaging   |
| 3. Intended use  | <b>Sealant for non-structural use in joints in buildings and pedestrian walkways Part 2: Sealants for Glazing elements</b> |
| 4. Manufacturer  | <b>Everbuild Building Products Ltd, Site 41, Cross Green Industrial Estate, Knowsthorpe Way, Leeds, LS9 0SW</b>            |
| 5. Authorised Representative                               | <b>Not Applicable</b>  |
| 6. Assessment and Verification of Constancy of Performance | <b>System 3</b>  |
| 7. Notified Body and Tasks                                 | <b>Ginger CEBTP Notified Body No. 00074</b>  |
| 8. European Technical Assessment                           | <b>Not Applicable</b>  |
| 9. Declared Performance                                    | <b>TO EN15651-2 (2012)</b>   |



**Building & DIY Products You Can Trust**

Site 41, Knowsthorpe Way,

Cross Green Industrial Estate, Leeds, LS9 0SW

Telephone: +44 (0) 113 240 3456 Sales: +44 (0) 113 240 2424

Fax: +44 (0) 113 240 0024

e-mail: [info@everbuild.co.uk](mailto:info@everbuild.co.uk)

website: [www.everbuild.co.uk](http://www.everbuild.co.uk)

|   |                 |
|---|-----------------|
| Type  | <b>G-CC</b>     |
| Classification  | <b>G25LM</b>    |
| Reaction to Fire  | <b>Class E</b>  |
| Loss of Volume ISO10563   | <b>≤10%</b>     |
| Resistance to flow ISO7390  | <b>≤3 mm</b>    |
| Adhesion/cohesion properties at maintained extension after water immersion (23°C) ISO 10590 | <b>NF</b>       |
| Adhesion/cohesion properties after exposure to heat, water and artificial light ISO 11431   | <b>NF</b>       |
| Elastic recovery ISO 7389   | <b>≥60%</b>     |
| Adhesion/cohesion properties (-30°C) ISO 8339 modified                                      | <b>≤0.9 MPa</b> |
| Adhesion/cohesion properties at maintained extension (-30°C) ISO 8340                       | <b>NF</b>       |
| Durability ISO 8340, ISO 9047 and ISO 10590   | <b>Pass</b>     |

Substrate: Anodised aluminium

Primer: Silicone Primer NP2

|                                     |   |
|-------------------------------------|---|
| 1. Identification Code              | <b>Everbuild 825 Silicone Sealant;</b><br><b>Codes:</b>   |
| 2. Type, Batch and/or Serial Number | <b>- For batch number - see packaging</b>   |
| 3. Intended use                     | <b>Sealant for non-structural use in joints in buildings and pedestrian walkways Part 3: Sealants for Sanitary elements</b> |



**Building & DIY Products You Can Trust**

Site 41, Knowsthorpe Way,  
 Cross Green Industrial Estate, Leeds, LS9 0SW  
 Telephone: +44 (0) 113 240 3456 Sales: +44 (0) 113 240 2424  
 Fax: +44 (0) 113 240 0024  
 e-mail: info@everbuild.co.uk  
 website: www.everbuild.co.uk

|   |   |
|---|---|
| 4. Manufacturer   | <b>Everbuild Building Products Ltd, Site 41, Cross Green Industrial Estate, Knowsthorpe Way, Leeds, LS9 0SW</b> |
| 5. Authorised Representative  | <b>Not Applicable</b>   |
| 6. Assessment and Verification of Constancy of Performance                                  | <b>System 3</b>   |
| 7. Notified Body and Tasks  | <b>Ginger CEBTP Notified Body No. 00074</b>   |
| 8. European Technical Assessment  | <b>Not Applicable</b>   |
| 9. Declared Performance   | <b>TO EN15651-3 (2012)</b>  |
| Type  | <b>S</b>  |
| Classification  | <b>XS2</b>  |
| Reaction to Fire  | <b>Class E</b>  |
| Loss of Volume ISO10563   | <b>≤20%</b>   |
| Resistance to flow ISO7390  | <b>≤3 mm</b>  |
| Adhesion/cohesion properties at maintained extension after water immersion (23°C) ISO 10590 | <b>NF</b>   |
| Action of the microorganisms : Intensity of growth ISO 846, method B                        | <b>2</b>  |
| Durability ISO 846, method B, ISO 8340, ISO 9047 and ISO 10590                              | <b>Pass</b>   |

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9 . The declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.



**Building & DIY Products You Can Trust**

Site 41, Knowsthorpe Way,

Cross Green Industrial Estate, Leeds, LS9 0SW

Telephone: +44 (0) 113 240 3456 Sales: +44 (0) 113 240 2424

Fax: +44 (0) 113 240 0024

e-mail: [info@everbuild.co.uk](mailto:info@everbuild.co.uk)

website: [www.everbuild.co.uk](http://www.everbuild.co.uk)

Signed: I. G. Southerington – Head of Technical

P.R. Thomas – Technical Manager

Two handwritten signatures in blue ink. The first signature, on the left, is for I. G. Southerington and is highly stylized. The second signature, on the right, is for P.R. Thomas and is also stylized.

Dated: Leeds, 24/2/14