

TECHNICAL DATA



Aluminium Wood Primer

Code 8919 **5 litres**

DESCRIPTION

A solvent-borne blend of fine grade aluminium and high quality resin. Formulated for interior and exterior use on new or bare timber. It provides a barrier against the oily exudations of naturally resinous timber and can be used as a sealer on weathered creosote or smoke damaged surfaces and is also self-knotting.

PREPARATION

All surfaces to be painted should be clean, dry and free from loose and flaking material. Wash down oily timbers such as teak with White Spirit and allow to dry. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Special precautions should be taken during surface preparation of pre-1960's paint surfaces over wood and metal as they may contain harmful lead. For further advice contact our Technical Department.

APPLICATION

Stir well before use. Easy to apply by brush, paying particular attention to the end grain.

COVERAGE

Aluminium Wood Primer will cover at the rate of approximately 13-15 square metres per litre depending on the nature and porosity of the surface being painted.

DRYING TIME

Touch dry in 4-6 hours. Recoatable after 16-24 hours.

FILM THICKNESS

Wet: 75µm, dry: 28µm.

VOLUME SOLID

37%.

COLOUR & FINISH

Metallic Grey, Matt finish.

SIZE

5 litres.

VOC CONTENT

HIGH VOC CONTENT 25-50%.

VOC's (Volatile Organic Compounds) contribute to atmospheric pollution.

EU limit value for this product (Cat A/g): 450g/l (2007).

This product contains maximum 400g/l VOC.

CLEANING

Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

TRANSPORTATION & STORAGE

To avoid risk of spilling, always store and transport in a secure upright position.

PROTECT FROM FROST.

All products supplied by Biokil Crown Ltd are of high quality. The Company however cannot govern the conditions of usage and application of its products and any warrant written or implied covers materials only. The information contained in this leaflet is given in good faith but no liability can be assumed by the Company for any damage, loss or injury or patent infringement arising from its use.



TECHNICAL DATA



PRECAUTIONS

PAINT UN1263.

FLAMMABLE.

Contains White Spirit.

DANGEROUS FOR THE ENVIRONMENT

Toxic to aquatic organisms. May cause long term adverse effects in the aquatic environment.

Avoid release to the environment.

Contains Cobalt Carboxylate. May produce an allergic reaction.

Keep away from sources of ignition – No smoking.

Repeated exposure may cause skin dryness or cracking.

Ensure maximum ventilation during application and drying.

Avoid contact with skin and eyes.

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

After contact with skin, wash immediately with plenty of soap and water or a recognized skin cleaner – DO

NOT USE SOLVENT OR THINNERS.

When applying to large interior surfaces or in confined spaces, wear a suitable cartridge respirator or air fed respiratory protective equipment.

If swallowed, seek medical advice immediately and show this container or label.

Keep out of the reach of children.