

TECHNICAL DATA SHEET

FLOOR PAINT

DESCRIPTION

An air-drying solvent-based semi-gloss finish based on a durable alkyd resin.

USES

Suitable for use on concrete and wooden floors in garages, factories and workshops. It can also be used on some asphalt floors, but a test application should be made to a small area to ensure that the asphalt is not softened or otherwise affected, and that the paint dries and hardens satisfactorily.

RECOMMENDED USES

Interior walkways and garage floors.

TYPE OF SUBSTRATE

Concrete, and wooden floors. Also suitable for use on some asphalt floors. For further advice on other substrates contact our Technical Department.

COLOUR RANGE

Red, Light Grey and Dark Grey.

PACKAGING

5 Litre.

FINISH

Mid Sheen.

COVERAGE

Approximately 11 square metres per litre, depending on the nature and porosity of the surface being painted.

DRYING TIME

Touch dry in 3 hours. Recoatable after 16-24 hours.

TRANSPORTATION & STORAGE

To avoid the risk of spillage, always store and transport in a secure upright position.
STORE AWAY FROM HEAT AND FLAME.

THINNER

White Spirit.

PREPARATION

All surfaces to be painted should be clean, dry and free from loose and flaking materials. If the surface requires cleaning - this can be done by using a heavy duty degreasing agent for removing oil, grease and dirt from concrete floors. New concrete floors should preferably be allowed to mature for several months before painting. Concrete surfaces should also be free of dust, grit, cement fines and laitance. Very dense, smooth concrete surfaces (such as power floated concrete) normally require to be acid etched before painting in order to promote satisfactory adhesion. Special precautions should be taken during surface preparation of pre-1960's paint surfaces over wood and metal as they may contain harmful lead. For further advice contact our Technical Department.

APPLICATION INSTRUCTIONS

Stir well before use. Apply two coats, allowing overnight drying between coats under normal drying conditions. To assist drying time, the first coat must be thinned with up to 20% by volume of White Spirit.

CLEANING

Remove as much product as possible from application equipment before washing. Replace lid firmly. Wash equipment immediately after use with White Spirit or Turpentine Substitute. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

All products supplied by DIY Refurb are of high quality. The Company cannot however govern the conditions of usage and application of its products. All recommendations are made without warranty or guarantee since the conditions of use are beyond our control. The information contained in this leaflet is given in good faith but no liability can be assumed by the Company for any damage, loss or injury or patent infringement arising from its use.

www.diyrefurb.com

Telephone 0800 1114898

Email: sales@diyrefurb.com

DIY Refurb is a trading name of Refurb (Holdings) Limited 15 & 17 Church Street Stourbridge West Midlands DY8 1LU



TECHNICAL DATA SHEET

PRECAUTIONS

PAINT PRODUCT

FLAMMABLE

Contains Cobalt Carboxylate and Ethyl Methyl Ketoxime.

May produce an allergic reaction.

Repeated exposure may cause skin dryness or cracking.

Keep away from sources of ignition - No Smoking.

Ensure maximum ventilation during application and drying.

Avoid contact with skin and eyes.

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

After contact with skin, wash immediately with plenty of soap and water or a recognised skin cleaner - DO NOT USE SOLVENT OR THINNERS.

When applying by brush or roller to large interior surfaces or in confined spaces, wear a suitable cartridge respirator or air fed respiratory protective equipment.

If swallowed, seek medical advice immediately and show the container or label.

Keep out of reach of children.

HEALTH & SAFETY

Material Safety Data Sheet available on request.

VOC CONTENT

HIGH VOC CONTENT 25-50%

VOC's (Volatile Organic Compounds) contribute to atmospheric pollution.