

## SAFETY DATA SHEET

### Siroflex Silicone Spray

#### SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

##### 1.1. Product identifier

Product name	Siroflex Silicone Spray
Product No.	SA1279

##### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses	Universal lubricant.
-----------------	----------------------

##### 1.3. Details of the supplier of the safety data sheet

Supplier	Siroflex Limited Dodworth Business Park Dodworth Barnsley S75 3SP Tel: 01226771600 Fax: 01226771601 www.siroflex.co.uk info@siroflex.co.uk
----------	--------------------------------------------------------------------------------------------------------------------------------------------------------------------

##### 1.4. Emergency telephone number

National Emergency Telephone Number  
UK + 44 (0) 1226 771600 (Office hours only)

#### SECTION 2: HAZARDS IDENTIFICATION

##### 2.1. Classification of the substance or mixture

Classification (EC 1272/2008)	Physical and Chemical Hazards	Flam. Aerosol 1 - H222
	Human health	Not classified.
	Environment	Aquatic Chronic 3 - H412
Classification (1999/45/EEC)	F+;R12. R52/53.	

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

##### Human health

In high concentrations, vapours and spray mists are narcotic and may cause headache, fatigue, dizziness and nausea.

##### Environment

The product contains a substance which is harmful to aquatic organisms and which may cause long term adverse effects in the aquatic environment.

##### Physical and Chemical Hazards

Pressurised container: Must not be exposed to temperatures above 50°C. The product is extremely flammable, and explosive vapour/air mixtures may be formed even at normal room temperatures

##### 2.2. Label elements

Contains	Low boiling Point Hydrogen Treated Naphtha- Naphtha (Petroleum) Hydrotreated Light
Label In Accordance With (EC) No. 1272/2008	



Signal Word

Danger

## Siroflex Silicone Spray

### Hazard Statements

H222	Extremely flammable aerosol.
H412	Harmful to aquatic life with long lasting effects.

### Precautionary Statements

P210	Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Pressurized container: Do not pierce or burn, even after use.
P261	Avoid breathing vapour/spray.
P410+412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F.

### Supplementary Precautionary Statements

P273	Avoid release to the environment.
P501	Dispose of contents/container in accordance with national regulations.

### 2.3. Other hazards

H229 Pressurised container: May burst if heated.

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.2. Mixtures

PROPANE	30-60%
CAS-No.: 74-98-6	EC No.: 200-827-9
	Registration Number: 01-2119486944-21
Classification (EC 1272/2008) Flam. Gas 1 - H220	Classification (67/548/EEC) F+R12
BUTANE/ISOBUTANE	30-60%
CAS-No.: 106-97-8	EC No.: 203-448-7
	Registration Number: 01-2119474691-32
Classification (EC 1272/2008) Flam. Gas 1 - H220	Classification (67/548/EEC) F+R12
Low boiling Point Hydrogen Treated Naphtha- Naphtha (Petroleum) Hydrotreated Light	10-30%
CAS-No.: 64742-49-0	EC No.: 265-151-9
	Registration Number: 01-2119475133-43
Classification (EC 1272/2008) Flam. Liq. 2 - H225 Skin Irrit. 2 - H315 STOT SE 3 - H336 Asp. Tox. 1 - H304	Classification (67/548/EEC) Xn;R65. Xi;R38. F;R11. N;R51/53.
HEXANE-norm	< 1%
CAS-No.: 110-54-3	EC No.: 203-777-6
	Registration Number: 01-2119480412-44-0000

## Siroflex Silicone Spray

Classification (EC 1272/2008)	Classification (67/548/EEC)
Flam. Liq. 2 - H225	F;R11
Skin Irrit. 2 - H315	Repr. Cat. 3;R62
Repr. 2 - H361f	Xn;R48/20,R65
STOT SE 3 - H336	Xi;R38
STOT RE 2 - H373	R67

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

### SECTION 4: FIRST AID MEASURES

#### 4.1. Description of first aid measures

##### General information

Move the exposed person to fresh air at once.

##### Inhalation

Move the exposed person to fresh air at once. Perform artificial respiration if breathing has stopped. Keep the affected person warm and at rest. Get prompt medical attention.

##### Ingestion

Immediately rinse mouth and provide fresh air. Do not induce vomiting. Get medical attention if any discomfort continues.

##### Skin contact

Wash skin with soap and water. Get medical attention if any discomfort continues.

##### Eye contact

Immediately rinse with water. Continue to rinse for at least 15 minutes. Make sure to remove any contact lenses from the eyes before rinsing. Get medical attention promptly if symptoms occur after washing.

#### 4.2. Most important symptoms and effects, both acute and delayed

##### General information

Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.

##### Inhalation

Vapours may cause drowsiness and dizziness. There may be a feeling of tightness in the chest with shortness of breath.

##### Ingestion

There may be soreness and redness of the mouth and throat. Fumes from the stomach contents may be inhaled resulting in the same symptoms as inhalation.

##### Skin contact

Skin irritation.

##### Eye contact

Prolonged contact may cause redness and/or tearing.

#### 4.3. Indication of any immediate medical attention and special treatment needed

### SECTION 5: FIREFIGHTING MEASURES

#### 5.1. Extinguishing media

##### Extinguishing media

Extinguish with alcohol-resistant foam, carbon dioxide or dry powder. Cool aerosol containers exposed to heat with water spray and remove container, if no risk is involved.

##### Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

#### 5.2. Special hazards arising from the substance or mixture

##### Hazardous combustion products

Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

##### Unusual Fire & Explosion Hazards

Extremely flammable. Forms explosive mixtures with air. May explode in a fire. Vapours are heavier than air and may spread near ground to sources of ignition.

##### Specific hazards

Pressurised container: Must not be exposed to temperatures above 50°C.

# Siroflex Silicone Spray

## 5.3. Advice for firefighters

Special Fire Fighting Procedures

Use water spray to reduce vapours. Aerosol cans may explode in a fire. Cool aerosol containers exposed to heat with water spray and remove container, if no risk is involved

Protective equipment for fire-fighters

Self contained breathing apparatus and full protective clothing must be worn in case of fire.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

### 6.1. Personal precautions, protective equipment and emergency procedures

Ensure suitable personal protection (including respiratory protection) during removal of spillages in a confined area.

### 6.2. Environmental precautions

Avoid discharge into drains.

### 6.3. Methods and material for containment and cleaning up

Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Absorb in vermiculite, dry sand or earth and place into containers.

Provide ventilation and confine spill. Do not allow runoff to sewer

### 6.4. Reference to other sections

Wear protective clothing as described in Section 8 of this safety data sheet. For waste disposal, see section 13.

## SECTION 7: HANDLING AND STORAGE

### 7.1. Precautions for safe handling

Keep away from heat, sparks and open flame. Read and follow manufacturer's recommendations. Avoid inhalation of vapours and spray mists. Do not spray on a naked flame or any incandescent material. When sprayed on a naked flame or any incandescent material the aerosol vapours can be ignited.

### 7.2. Conditions for safe storage, including any incompatibilities

Extremely flammable. Store at moderate temperatures in dry, well ventilated area. Keep away from heat, sparks and open flame. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn even after use

Storage Class

Extremely Flammable Aerosol

### 7.3. Specific end use(s)

Silicone based lubricant

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1. Control parameters

Name	STD	TWA - 8 Hrs		STEL - 15 Min		Notes
BUTANE/ISOBUTANE	WEL	600 ppm		750 ppm		
HEXANE-norm	WEL	20 ppm	72 mg/m3			
Low boiling Point Hydrogen Treated Naphtha- Naphtha (Petroleum) Hydro-treated Light			1000 mg/m3		1000 mg/m3	
PROPANE	WEL	1000 ppm	1800 mg/m3			

WEL = Workplace Exposure Limit.

### 8.2. Exposure controls

Protective equipment

## Siroflex Silicone Spray



Process conditions

Ensure suitable ventilation of area.

Engineering measures

Provide adequate ventilation.

Respiratory equipment

No specific recommendation made, but respiratory protection must be used if the general level exceeds the recommended occupational exposure limit. In case of inadequate ventilation use suitable respirator

Hand protection

For prolonged or repeated skin contact use suitable protective gloves. The most suitable glove must be chosen in consultation with the gloves supplier, who can inform about the breakthrough time of the glove material

Eye protection

Wear approved chemical safety goggles where eye exposure is reasonably probable.

Other Protection

Provide eyewash station.

Hygiene measures

When using do not eat, drink or smoke. Wash promptly if skin becomes wet or contaminated.

Personal protection

Wear protective work clothing.

Skin protection

Wear suitable gloves if prolonged or repeated skin contact is likely

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on basic physical and chemical properties

Appearance	Aerosol container containing a mixture of active ingredients, solvents and propellants
Colour	Colourless.
Odour	Hydrocarbon.
Solubility	Insoluble in water
Flash point (°C)	<-40°C
Auto Ignition Temperature (°C)	410-580
Flammability Limit - Lower(%)	1.8%
Flammability Limit - Upper(%)	9.5%
Comments	Information given concerns the major ingredient. A flash point method is not available for aerosols but the major hazardous component, the Propellant has a flash point of <-40 C with flammability limits of 9.5% vol. upper and 1.8% vol. lower. Auto ignition temperature is 410/580 C

### 9.2. Other information

Not available.

## SECTION 10: STABILITY AND REACTIVITY

### 10.1. Reactivity

Stable under recommended transport or storage conditions.

### 10.2. Chemical stability

Highly volatile.

### 10.3. Possibility of hazardous reactions

No known hazardous reactions if stored under normal conditions.

Hazardous Polymerisation

Will not polymerise.

# Siroflex Silicone Spray

## 10.4. Conditions to avoid

Avoid heat, flames and other sources of ignition. Avoid exposure to high temperatures or direct sunlight.

## 10.5. Incompatible materials

Materials To Avoid

No incompatible groups noted.

## 10.6. Hazardous decomposition products

None under normal conditions. In case of fire, toxic gases (CO, CO<sub>2</sub>, NO<sub>x</sub>) may be formed.

## **SECTION 11: TOXICOLOGICAL INFORMATION**

### 11.1. Information on toxicological effects

General information

Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.

Inhalation

Contains organic solvents which in case of overexposure may depress the central nervous system causing dizziness and intoxication. High exposures may cause an abnormal heart rhythm and prove suddenly fatal. Very high atmospheric concentrations may cause anaesthetic effects and asphyxiation.

Ingestion

May cause soreness and redness of mouth and throat.

Skin contact

Prolonged and frequent contact may cause redness and irritation.

Eye contact

Spray and vapour in the eyes may cause irritation and smarting.

Health Warnings

In high concentrations, vapours are narcotic and may cause headache, fatigue, dizziness and nausea. Arrhythmia, (deviation from normal heart beat).

Route of entry

Inhalation.

Target Organs

Central nervous system Respiratory system, lungs

Medical Symptoms

Narcotic effect. Vapours may cause drowsiness and dizziness.

## **SECTION 12: ECOLOGICAL INFORMATION**

Ecotoxicity

The product contains a substance which is harmful to aquatic organisms and which may cause long term adverse effects in the aquatic environment. Dangerous for the environment if discharged into watercourses. Do not allow to enter drains, sewers or watercourses

### 12.1. Toxicity

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

### 12.2. Persistence and degradability

No data available.

Degradability

There are no data on the degradability of this product.

### 12.3. Bioaccumulative potential

# Siroflex Silicone Spray

Bioaccumulative potential

No data available on bioaccumulation.

## 12.4. Mobility in soil

Mobility:

The product contains volatile organic compounds (VOC) which will evaporate easily from all surfaces. The product is insoluble in water and will spread on the water surface

## 12.5. Results of PBT and vPvB assessment

Not determined

## 12.6. Other adverse effects

None known.

---

## **SECTION 13: DISPOSAL CONSIDERATIONS**

---

General information

Ensure containers are empty before discarding (explosion risk). Do not puncture or incinerate even when empty. Dispose of waste and residues in accordance with local authority requirements

### 13.1. Waste treatment methods

Make sure containers are empty before discarding (explosion risk). Do not puncture or incinerate even when empty. Dispose of waste and residues in accordance with local authority requirements

Waste Class

Full or Partially Empty Aerosol: 16 05 04, Empty Aerosol: 15 01 10 (Containing hazardous residues). Empty Aerosol: 15 01 04 (No hazardous residues).

---

## **SECTION 14: TRANSPORT INFORMATION**

---

General

This product is packed in accordance with the Limited quantity Provisions of CDGCPL2, ADR and IMDG. These provisions allow the transport of aerosols of less than 1 litre packed in cartons of less than 30kg gross weight to be exempt from control providing they are labelled in accordance with the requirements of those regulations to show that they are transported as Limited Quantities. Aerosols not so packed must show the following.

### 14.1. UN number

UN No. (ADR/RID/ADN)	1950
UN No. (IMDG)	1950
UN No. (ICAO)	1950

### 14.2. UN proper shipping name

Proper Shipping Name                      AEROSOLS

### 14.3. Transport hazard class(es)

ADR/RID/ADN Class	2, 5F
ADR/RID/ADN Class	Class 2: Gases
ADR Label No.	2.1
IMDG Class	2.1
ICAO Class/Division	2.1
Transport Labels	



# Siroflex Silicone Spray

## 14.4. Packing group

ADR/RID/ADN Packing group	#
IMDG Packing group	#
ICAO Packing group	#

## 14.5. Environmental hazards

Environmentally Hazardous Substance/Marine Pollutant  
No.

## 14.6. Special precautions for user

EMS	F-D, S-U
Tunnel Restriction Code	(D)

## 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not applicable.

## **SECTION 15: REGULATORY INFORMATION**

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Uk Regulatory References

Health and Safety at Work Act 1974. Chemicals (Hazard Information & Packaging) Regulations. The Control of Substances Hazardous to Health Regulations 2002 (S.I. 2002 No. 2677) with amendments  
Statutory Instruments

Control of Substances Hazardous to Health.

Approved Code Of Practice

Safety Data Sheets for Substances and Preparations. Classification and Labelling of Substances and Preparations Dangerous for Supply.

Guidance Notes

ECHA: Guidance on the Compilation of safety data sheets. (V1.1, December 2011)

EU Legislation

Dangerous Preparations Directive 1999/45/EC. Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 with amendments. Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, including amendments. Commission Directive 91/322/EEC of 29 May 1991 on establishing indicative limit values by implementing Council Directive 80/147/EEC on the protection of workers from the risks related to exposure to National Regulations

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (S.I. 2009 No. 716). The Aerosol Dispensers Regulations 2009 (SI 2824) The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment Regulations 2009 ("CDG 2009"), SI 2009 No 1348 Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and Authorisations (Title VII Regulation 1907/2006)

No specific authorisations are noted for this product.

Restrictions (Title VIII Regulation 1907/2006)

No specific restrictions of use are noted for this product.

### 15.2. Chemical Safety Assessment

No chemical safety assessment has been carried out.

## **SECTION 16: OTHER INFORMATION**

Issued By Technical Service Manager



## Siroflex Silicone Spray

Revision Date 27-10-2014  
Revision 5  
Supersedes date 11-11-2013  
SDS No. 10464  
Date 27-10-2014

### Risk Phrases In Full

R12 Extremely flammable.  
R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.  
R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.  
R65 Harmful: may cause lung damage if swallowed.  
R11 Highly flammable  
R38 Irritating to skin.  
R62 Possible risk of impaired fertility.  
R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.  
R67 Vapours may cause drowsiness and dizziness.

### Hazard Statements In Full

H315 Causes skin irritation.  
H280 Contains gas under pressure; may explode if heated.  
H222 Extremely flammable aerosol.  
H220 Extremely flammable gas.  
H412 Harmful to aquatic life with long lasting effects.  
H225 Highly flammable liquid and vapour.  
H304 May be fatal if swallowed and enters airways.  
H373 May cause damage to organs <<Organs>> through prolonged or repeated exposure.  
H336 May cause drowsiness or dizziness.  
H361f Suspected of damaging fertility.  
H411 Toxic to aquatic life with long lasting effects.

### Disclaimer

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his