

TECHNICAL DATA



Wood Primer Undercoat

Code 841 (5litre)

DESCRIPTION

Wood Primer Undercoat is specially formulated to provide a dense covering basecoat to wood and metal surfaces, with outstanding opacity and excellent application properties, making it ideal for interior and exterior new work application.

USES

When applied over suitably prepared and primed surfaces, provides the ideal foundation for overcoating with Trade Gloss. Suitable for interior and exterior use.

RECOMMENDED USES

Interior and exterior.

TYPE OF SUBSTRATE

Wood and metal. Also suitable for use on plaster, wallboards, concrete, cement rendering, brickwork and blockwork.

COLOUR RANGE

Brilliant White.

FINISH

Semi-matt.

COVERAGE

Approximately 14 square metres per litre depending on the nature and porosity of the surface being painted.

DRYING TIME

Touch dry in 4-6 hours. Recoatable after 16-24 hours.

TRANSPORTATION & STORAGE

To avoid the risk of spillage, always store and transport in a secure upright position.

STORE AWAY FROM HEAT AND FLAME.

THINNER

White Spirit.

PREPARATION

All surfaces to be painted should be clean, dry and free from loose and flaking materials. Prime bare surfaces with the appropriate Leyland Primer. Rub down previously painted surfaces with fine waterproof abrasive paper and rinse thoroughly. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Special precautions should be taken during surface preparation of pre-1960's paint surfaces over wood and metal as they may contain harmful lead. For further advice contact Technical Advisory.

APPLICATION INSTRUCTIONS

Stir well. Easy to apply by brush, roller or spray. Do not apply over polystyrene surfaces.

All products supplied by Biokil Crown Ltd are of high quality. The Company however cannot govern the conditions of usage and application of its products and any warrant written or implied covers materials only. The information contained in this leaflet is given in good faith but no liability can be assumed by the Company for any damage, loss or injury or patent infringement arising from its use.



TECHNICAL DATA



CLEANING

Remove as much product as possible from application equipment before washing. Replace lid firmly. Wash equipment immediately after use with White Spirit or Turpentine Substitute. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

PRECAUTIONS

PAINT PRODUCT

FLAMMABLE

Contains Ethyl Methyl Ketoxime.

May produce an allergic reaction.

Repeated exposure may cause skin dryness or cracking.

Keep away from sources of ignition - no smoking.

Ensure maximum ventilation during application and drying.

Avoid contact with skin and eyes.

In case of contact with eyes, rinse immediately with plenty of clean water and seek medical advice.

After contact with skin, wash immediately with plenty of soap and water or a recognised skin cleaner - DO NOT USE SOLVENT OR THINNERS.

When applying by brush or roller to large interior surfaces or in confined spaces, wear a suitable cartridge respirator or air fed respiratory protective equipment.

When spraying do not breathe spray, wear suitable respiratory protective equipment.

If swallowed, seek medical advice immediately and show the container or label.

Keep out of reach of children.

PROFESSIONAL DECORATORS

Safety data sheet available for professional user on request.

VOC CONTENT

HIGH VOC CONTENT 25-50%

VOC's (Volatile Organic Compounds)

contribute to atmospheric pollution.