

Mobility / On-board equipment / Hikvision / Recorders

AE-MN5043(M12)

HIKVISION



Features

- Hikvision
- NVR recorder for vehicle on-boarding
- 4 CH IPC with M12 connector
- Maximum resolution 1080p (1920x1080)
- Compression H.265/H.264
- Ethernet, WiFi and 4G communication
- GPS
- Alarms
- Audio
- Space for 2 HDD 2.5"

Specifications

Brand	Hikvision
Channels	4 IP channels with M12 connector
Main stream recording	1080P / 720P / WD1 / 4CIF
Sub stream recording	720P / WD1 / 4CIF / 2CIF / CIF
Video compression format	Video: H.265 / H.264 Audio: ADPCM,G.711U,G.711A
Display resolution	1080p (1920×1080), 720p (1280×720)
Dual stream recording	Supported
Audio	4 Input CH (With own video cable)
Audio Compression	G.711.A / G.711.U / G.711.1 / G.726
Video output	CVBS (M12) VGA
Display divisions	1 / 4 / 9
Recording method	Home/Manual/Programming/Alarm Event Logging
Alarm	Alarm pre-recording: 0-60 min Post-recording:: 0-30 min
External Backup	USB memory / HDD USB / CD-RW USB / DVR-RW USB
Internal memory	2x SATA 2.5" HDD or SSD up to 2 TB each HDD
	1x MicroSD up to 256 GB
Communication	3G/4G: EVDO/TD-SCDMA/WCDMA/TDD-LTE/FDD-LTE
	WiFi: Module WI58. Support: 802.11a/b/g/n/ac 2x 5.8G WiFi SMA antenna Frequency band: 2.4/5.0 GHz
Ports	1 x SIM Slot 1 x RS232 2 x RS422 1 x USB 2.0 1 x USB 2.0 (Aviation Connector 5pin)) 1 x MIC
Input sensors	4 high/low level input sensors
Alarms	4 Inputs and 2 Outputs
GPS	Positioning, speed detection and time synchronization
G-Sensor	Incorporated

Operating modes	Mouse, web page and touch screen
Power	DC 9~36 V, <0.5 W (standby), <45 W (Carga al máximo)
Temp. Funcionamiento	-10°C~60°C, Humedad 10~90%
Dimensiones / Peso	60.1 (Al) x 206 (An) x 225.4 (Fo) mm / 1.66 Kg (sin disco duro)