

IP CCTV / Professional IP cameras / Hikvision / Bullet Cameras

DS-2CD1047G2-L(2.8mm)

HIKVISION



Features

- Hikvision
- Value Range
- Bullet IP camera
- 1/3" Progressive Scan CMOS
- 4 Megapixel (2560x1440)
- 2.8 mm Lens
- 0 Lux
- White light range 30 m
- ColorVu: color image 24 hours
- Compression H.265+ / H.265 / H.264+ / H.264
- Motion detection 2.0
- WDR (120 dB)
- 3D DNR
- RJ-45 10/100M BaseT
- PoE IEEE802.3af
- WEB, CMS, Smartphone and NVR interface
- ONVIF Compatible
- Weatherproof IP67

Specifications

Brand	HIKVISION
Range	Value
Image sensor	1/3" Progressive Scan CMOS
Maximum resolution	4 Megapixel (2560x1440)
Main Stream rate	20 fps (2560x1440), 25 fps (1920x1080, 1280x720)
Extra Stream rate	25 fps (1280x720, 640x480, 640x360)
Compression	H.265+ / H.264+ / H.265 / H.264
Bitrate	32 Kbps ~ 8 Mbps
Lens	2.8 mm
Viewing Angle (FOV)	H: 96°, V: 52°, D: 113°
Range performance	64 m (D), 25 m (O), 12 m (R), 6 m (I)
Minimum illumination	Colour: 0.001 Lux @(F1.0, AGC ON) 0 Lux with white light, range 30 m
Day/Night	ColorVu: Color image 24 hours
Image improvements	WDR (120 dB), BLC, HLC, 3D-DNR, AWB, ROI, Mirror function, Privacy masking
Motion Detection	Motion detection 2.0 with human and vehicle classification applied in motion detection.
Internal memory	No
Network interface	Ethernet 10/100M BaseT
Remote access	Web Browser, Hik-Connect Smartphone App, PC Software iVMS-4200 and Hik-Central
Interoperability	ONVIF, ISAPI
Power	DC 12 V / 400 mA / 5 W max. / IEEE802.3af PoE
Degree of protection	Weatherproof IP67
Material	Metal and plastic
Temp. operation	-30° C ~ +60° C
Dimensions	Ø 76.6 mm x 164.4 mm (H)

Base dimensions

Ø base 70 mm / Ø entre tornillos 55 mm / 3 tornillos

Weight

430 g