IP CCTV / Professional IP cameras / Hikvision / Turret cameras

DS-2CD1321G0-I(2.8mm)

HIKVISION



Features

- Hikvision
- VALUE range
- Turret IP Camera
- 1/2.9" Progressive Scan CMOS
- 2 Megapixel (1920x1080)
- 2.8 mm Lens
- 0 Lux
- IR Range 20 m
- Compression H.265+ / H.265 / H.264+ / H.264
- DWDR
- 3D-DNR
- Web interface, CMS, Smartphone & NVR
- ONVIF compatible
- PoE (IEEE802.3af)
- Weatherproof IP67

Specifications

Brand	HIKVISION
Range	VALUE
Image sensor	1/2.9" Progressive Scan CMOS
Maximum resolution	2 Megapixel (1920x1080)
Main Stream rate	25 fps (1920×1080, 1280×720)
Extra Stream rate	25 fps (640×480, 640x360)
Compression	H.265+ / H.264+ / H.265 / H.264
Bitrate	32 Kbps ~ 8 Mbps
Lens	2.8 mm
Viewing Angle (FOV)	H: 94°, V: 51°, D: 112°
Range performance	48 m (D), 19 m (O), 9 m (R), 4 m (I)
Electronic Shutter	1/3~1/100.000 s
Minimum illumination	Colour: 0.01 Lux @(F2.2, AGC ON) 0 Lux with IR range 20 m
Day/Night	Removable mechanical ICR filter
Image improvements	DWDR, BLC, HLC, 3D-DNR, AGC, AWB, Mirror Effect
Motion Detection	Yes
Network interface	RJ45 Ethernet 10 / 100 BaseT
Remote access	Web Browser, Hik-Connect Smartphone App, PC Software iVMS-4200 and Hik-Central
Interoperability	ISAPI, SDK
Power supply	DC 12 V / 400 mA / 4.8 W max.
Degree of protection	Weatherproof IP67
Material	Plastic
Temp. operation	-30º C ~ +60º C
Dimensions	Ø 109.9 mm x 103.6 mm (H)

Base dimensions	Ø base 109.9 mm / Ø entre tornillos 85 mm / 3 tornillos
Weight	300 g